

DIN EN 1806:2006-10 (E)

Chimneys - Clay/ceramic flue blocks for single wall chimneys - Requirements and test methods

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Types of flue blocks | 10 |
| 5 | Materials | 11 |
| 5.1 | Flue blocks | 11 |
| 5.2 | Insulation | 11 |
| 5.2.1 | General | 11 |
| 5.2.2 | Shape | 12 |
| 5.2.3 | Thermal conductivity of insulation | 12 |
| 5.2.4 | Resistance to heat | 12 |
| 6 | Tolerances on dimensions | 12 |
| 6.1 | Internal transverse dimensions | 12 |
| 6.2 | Height | 12 |
| 6.3 | Angles | 12 |
| 6.4 | Straightness | 12 |
| 6.5 | Squareness of ends | 12 |
| 6.6 | Squareness of angles and flatness of walls | 12 |
| 6.7 | Joints | 12 |
| 6.8 | Bonding extension | 13 |
| 6.9 | Tolerance on insulation thickness | 13 |
| 7 | Proof load | 13 |
| 7.1 | Straight flue blocks | 13 |
| 7.2 | Angle flue blocks | 13 |
| 7.3 | Minimum load for inspection opening sections | 13 |
| 7.4 | Adhesion between outer wall and insulation | 14 |
| 8 | Gas tightness and thermal shock resistance | 14 |
| 8.1 | Straight flues blocks | 14 |
| 8.1.1 | General | 14 |
| 8.1.2 | Initial gas tightness | 14 |
| 8.1.3 | Thermal shock resistance | 14 |
| 8.1.4 | Final gas tightness after thermal shock testing | 14 |
| 8.2 | Angle flue blocks | 14 |
| 9 | Condensate resistance | 15 |
| 10 | Corrosion resistance | 15 |
| 11 | Water absorption and bulk density | 15 |
| 11.1 | General | 15 |
| 11.2 | Water absorption | 15 |
| 11.3 | Bulk density | 15 |

| | | |
|---------|--|----|
| 12 | Abrasion resistance | 16 |
| 13 | Flow resistance | 16 |
| 14 | Thermal resistance | 16 |
| 15 | Resistance to fire | 16 |
| 15.1 | Internal to external | 16 |
| 15.1.1 | Testing at normal operating conditions | 16 |
| 15.1.2 | Soot fire test | 16 |
| 15.2 | External to external | 16 |
| 16 | Resistance to freeze/thaw | 16 |
| 17 | Evaluation of conformity | 17 |
| 17.1 | General | 17 |
| 17.2 | Initial type testing | 17 |
| 17.3 | Further tests | 17 |
| 17.4 | Factory production control | 17 |
| 18 | Test methods | 18 |
| 18.1 | Internal transverse dimensions | 18 |
| 18.2 | Height | 18 |
| 18.3 | Angles | 18 |
| 18.4 | Straightness | 18 |
| 18.5 | Squareness of ends | 19 |
| 18.5.1 | Gauge test | 19 |
| 18.5.2 | Direct measurement test | 20 |
| 18.6 | Squareness of angles and flatness of walls | 21 |
| 18.7 | Proof load | 22 |
| 18.7.1 | Test sample | 22 |
| 18.7.2 | Testing equipment | 22 |
| 18.7.3 | Procedure | 22 |
| 18.8 | Thermal performance tests | 23 |
| 18.8.1 | Test equipment | 23 |
| 18.8.2 | Test flue | 24 |
| 18.8.3 | Procedure | 25 |
| 18.8.4 | Measurement of permeability rate | 29 |
| 18.9 | Corrosion resistance test | 30 |
| 18.9.1 | Test specimens | 30 |
| 18.9.2 | Test equipment | 30 |
| 18.9.3 | Procedure | 30 |
| 18.9.4 | Expression of results | 31 |
| 18.10 | Water absorption | 31 |
| 18.10.1 | Test specimen | 31 |
| 18.10.2 | Test equipment | 31 |
| 18.10.3 | Procedure | 31 |
| 18.10.4 | Expression of results | 31 |
| 18.11 | Bulk density | 32 |
| 18.11.1 | Test specimen | 32 |
| 18.11.2 | Test equipment | 32 |
| 18.11.3 | Procedure | 32 |
| 18.11.4 | Expression of results | 32 |
| 18.12 | Abrasion resistance | 32 |
| 18.12.1 | Test flue | 32 |
| 18.12.2 | Test equipment | 33 |
| 18.12.3 | Procedure | 33 |
| 18.13 | Condensate resistance test | 35 |
| 18.13.1 | Test section | 35 |
| 18.13.2 | Test apparatus | 35 |
| 18.13.3 | Procedure | 35 |

| | | |
|--|---|----|
| 18.13.4 | Expression of results | 35 |
| 18.14 | Adhesion test for insulation attached to outer wall of flue blocks | 36 |
| 18.14.1 | Test specimen | 36 |
| 18.14.2 | Testing procedure | 36 |
| 18.14.3 | Loading | 36 |
| 19 | Designation | 37 |
| 20 | Marking, labelling and packaging | 38 |
| Annex A (normative) Measurement of the coefficient of friction of chimneys | | 39 |
| Annex B (normative) Thermal resistance | | 41 |
| B.1 | Method 1 : simplified calculation for flue blocks without cavities | 41 |
| B.2 | Method 2 : thermal resistance of flue blocks with or without cavities | 41 |
| B.2.1 | General | 41 |
| B.2.2 | Data | 42 |
| B.2.3 | Specific conditions for the cavities | 43 |
| B.2.4 | Calculations | 46 |
| B.3 | Method Approximate thermal resistance values | 46 |
| Annex C (normative) Sampling procedures for an AQL of 10 % and Inspection Level S2 | | 47 |
| C.1 | Acceptability determination | 47 |
| C.1.1 | General | 47 |
| C.1.2 | Single sampling | 47 |
| C.1.3 | Double sampling | 47 |
| C.2 | Normal inspection | 47 |
| C.3 | Normal to reduced inspection | 49 |
| C.4 | Reduced to normal inspection | 49 |
| C.5 | Tightened inspection | 49 |
| C.6 | Tightened to normal inspection | 50 |
| C.7 | Discontinuation of inspection | 50 |
| Annex ZA (informative) Clauses of this European Standard addressing the provisions of EU Construction Products Directives | | 51 |
| ZA.1 | Scope and relevant characteristics | 51 |
| ZA.2 | Procedure of attestation of conformity of clay/ceramic flue blocks | 54 |
| ZA.2.1 | System of attestation of conformity | 54 |
| ZA.2.2 | EC certificate and declaration of conformity | 54 |
| ZA.3 | CE Marking and labelling | 55 |
| Bibliography | | 59 |