DIN EN 13126-8:2006-05 (E)

Building hardware - Requirements and test methods for windows and doors height windows - Part 8: Tilt & Turn, Tilt-First and Turn -Only hardware

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Classification 6
4.1 General 6
4.2 Category of use (1 - first digit) 6
4.3 Durability (2 - second digit) 6
4.4 Mass (3 - third digit) 6
4.5 Fire resistance (4 - fourth digit) 6
4.6 Safety in use (5 - fifth digit) 6
4.7 Corrosion resistance (6 - sixth digit) 6
4.8 Security (7 - seventh digit) 6
4.9 Applicable part (8 - eighth digit) 7
4.10 Test sizes (9 - ninth digit) 7
4.11 Example of classification for Tilt&Turn hardware 7

5 Requirements 8
5.1 General 8
5.2 Mechanical stability 8
5.2.1 Stability of the scissor stay 8
5.2.2 Mechanical strength of hinges 9
5.3 Durability 11
5.4 Admissible tolerances 11
5.4.1 Sash operation tolerance 11
5.4.2 Handle operation tolerance 11
5.4.3 Locking point variable tolerance 12
5.5 Resistance to additional loading 12
5.6 Minimum closing device resistance 12
5.7 Corrosion resistance 12
5.8 Resistance to other additional tests 13

6 Test equipment 13

7 Test procedures 13
7.1 Samples 13
7.2 Stability of hinge 13
7.3 Durability test - Tilt&Turn 13
7.3.1 General 13
7.3.2 Tilt&Turn cycles - Tilt-First cycles 14
7.3.3 Turn cycles (into 90° turn position) 15
7.3.4 Acceptance criteria 16
7.3.5 Additional loading test - 1 000 N 16
7.3.6 Reveal test for hardware without turn-restrictor 16
7.3.7 Test for hardware with turn-restrictor 18
7.3.8 Rebate-hindrance test 18
7.4 Durability test - Turn-Only hardware 19

7.5 Minimum closing device resistance test 19
7.6 Corrosion resistance 19

Annex A (informative) Typical test equipment 20

Annex B (normative) Flow chart of test procedures 21

Bibliography 22