

# DIN EN 846-8:2006-10 (E)

## Methods of test for ancillary components for masonry - Part 8: Determination of load capacity and load-deflection characteristics of joist hangers

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>3</b>	<b>Principle .....</b>	<b>4</b>
<b>4</b>	<b>Materials .....</b>	<b>5</b>
<b>4.1</b>	<b>Masonry units .....</b>	<b>5</b>
<b>4.2</b>	<b>Mortar .....</b>	<b>5</b>
<b>4.3</b>	<b>Timber joists .....</b>	<b>5</b>
<b>4.4</b>	<b>Screws, nails, grouts, plugs, slot sections or other fixing ancillary items .....</b>	<b>5</b>
<b>5</b>	<b>Apparatus .....</b>	<b>6</b>
<b>6</b>	<b>Test specimens .....</b>	<b>7</b>
<b>6.1</b>	<b>Sampling .....</b>	<b>7</b>
<b>6.2</b>	<b>Construction and storage .....</b>	<b>7</b>
<b>7</b>	<b>Procedure .....</b>	<b>9</b>
<b>8</b>	<b>Expression of results .....</b>	<b>9</b>
<b>9</b>	<b>Evaluation of results .....</b>	<b>9</b>
<b>10</b>	<b>Test report .....</b>	<b>10</b>