ISO 5658-2:2006-09 (E)

Reaction to fire tests - Spread of flame - Part 2: Lateral spread on building and transport products in vertical configuration

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Definitions 1

4 Principle 3

5 Suitability of a product for testing 4
5.1 Surface characteristics 4
5.2 Thermally unstable products 5

6 Test specimens 5
6.1 Exposed surface 5
6.2 Number and size of specimens 5
6.3 Construction of specimens 7
6.4 Conditioning 7
6.5 Preparation 7

7 Test apparatus 9
7.1 General 9
7.2 The radiant panel support framework 10
7.3 Specimen support framework 11
7.4 Specimen holder 11
7.5 Pilot flame burner 12

8 Test environment 15

9 Additional equipment and instrumentation 15
9.1 Heat-flux meter 15
9.2 Total radiation pyrometer 16
9.3 Recorder 16
9.4 Timing devices 16
9.5 Dummy specimen 16
9.6 Calibration board 16
9.7 Backing boards and spacers 17

10 Setting-up and calibration procedure 17
10.1 Setting-up 17
10.2 Verification 20
10.3 Adjustment of the pilot flame 20

11 Test procedure 20

12 Expression of fire performance of a product 22

13 Test report 22

Annex A (normative) Safety precautions 24

Annex B (informative) Specimen construction 25

Annex C (informative) Calibration of the working heat-flux meter 26

Annex D (informative) Guidelines for reporting and follow-up of results of fire test procedures 27

Annex E (informative) Variability of test results 28

Annex F (normative) Test method for flame spread of plastic piping 31

Bibliography 33