

# ISO 5658-2:2006-09 (E)

## Reaction to fire tests - Spread of flame - Part 2: Lateral spread on building and transport products in vertical configuration

---

| <b>Contents</b>    |   | <b>Page</b> |
|--------------------|---|-------------|
| Foreword .....     |   | v           |
| Introduction ..... |   | vi          |
| 1                  | Scope .....                                       | 1           |
| 2                  | Normative references .....                        | 1           |
| 3                  | Definitions .....                                 | 1           |
| 4                  | Principle .....                                   | 3           |
| 5                  | Suitability of a product for testing .....        | 4           |
| 5.1                | Surface characteristics .....                     | 4           |
| 5.2                | Thermally unstable products .....                 | 5           |
| 6                  | Test specimens .....                              | 5           |
| 6.1                | Exposed surface .....                             | 5           |
| 6.2                | Number and size of specimens .....                | 5           |
| 6.3                | Construction of specimens .....                   | 7           |
| 6.4                | Conditioning .....                                | 7           |
| 6.5                | Preparation .....                                 | 7           |
| 7                  | Test apparatus .....                              | 9           |
| 7.1                | General .....                                     | 9           |
| 7.2                | The radiant panel support framework .....         | 10          |
| 7.3                | Specimen support framework .....                  | 11          |
| 7.4                | Specimen holder .....                             | 11          |
| 7.5                | Pilot flame burner .....                          | 12          |
| 8                  | Test environment .....                            | 15          |
| 9                  | Additional equipment and instrumentation .....    | 15          |
| 9.1                | Heat-flux meter .....                             | 15          |
| 9.2                | Total radiation pyrometer .....                   | 16          |
| 9.3                | Recorder .....                                    | 16          |
| 9.4                | Timing devices .....                              | 16          |
| 9.5                | Dummy specimen .....                              | 16          |
| 9.6                | Calibration board .....                           | 16          |
| 9.7                | Backing boards and spacers .....                  | 17          |
| 10                 | Setting-up and calibration procedure .....        | 17          |
| 10.1               | Setting-up .....                                  | 17          |
| 10.2               | Verification .....                                | 20          |
| 10.3               | Adjustment of the pilot flame .....               | 20          |
| 11                 | Test procedure .....                              | 20          |
| 12                 | Expression of fire performance of a product ..... | 22          |
| 13                 | Test report .....                                 | 22          |

|  |           |
|--|-----------|
| <b>Annex A (normative) Safety precautions .....</b>  | <b>24</b> |
| <b>Annex B (informative) Specimen construction .....</b>   | <b>25</b> |
| <b>Annex C (informative) Calibration of the working heat-flux meter .....</b>                                | <b>26</b> |
| <b>Annex D (informative) Guidelines for reporting and follow-up of results of fire test procedures .....</b> | <b>27</b> |
| <b>Annex E (informative) Variability of test results .....</b>   | <b>28</b> |
| <b>Annex F (normative) Test method for flame spread of plastic piping .....</b>                              | <b>31</b> |
| <b>Bibliography .....</b>  | <b>33</b> |