

ISO 5658-2:2006-09 (E)

Reaction to fire tests - Spread of flame - Part 2: Lateral spread on building and transport products in vertical configuration

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Definitions | 1 |
| 4 | Principle | 3 |
| 5 | Suitability of a product for testing | 4 |
| 5.1 | Surface characteristics | 4 |
| 5.2 | Thermally unstable products | 5 |
| 6 | Test specimens | 5 |
| 6.1 | Exposed surface | 5 |
| 6.2 | Number and size of specimens | 5 |
| 6.3 | Construction of specimens | 7 |
| 6.4 | Conditioning | 7 |
| 6.5 | Preparation | 7 |
| 7 | Test apparatus | 9 |
| 7.1 | General | 9 |
| 7.2 | The radiant panel support framework | 10 |
| 7.3 | Specimen support framework | 11 |
| 7.4 | Specimen holder | 11 |
| 7.5 | Pilot flame burner | 12 |
| 8 | Test environment | 15 |
| 9 | Additional equipment and instrumentation | 15 |
| 9.1 | Heat-flux meter | 15 |
| 9.2 | Total radiation pyrometer | 16 |
| 9.3 | Recorder | 16 |
| 9.4 | Timing devices | 16 |
| 9.5 | Dummy specimen | 16 |
| 9.6 | Calibration board | 16 |
| 9.7 | Backing boards and spacers | 17 |
| 10 | Setting-up and calibration procedure | 17 |
| 10.1 | Setting-up | 17 |
| 10.2 | Verification | 20 |
| 10.3 | Adjustment of the pilot flame | 20 |
| 11 | Test procedure | 20 |
| 12 | Expression of fire performance of a product | 22 |
| 13 | Test report | 22 |

| | |
|--|-----------|
| Annex A (normative) Safety precautions | 24 |
| Annex B (informative) Specimen construction | 25 |
| Annex C (informative) Calibration of the working heat-flux meter | 26 |
| Annex D (informative) Guidelines for reporting and follow-up of results of fire test procedures | 27 |
| Annex E (informative) Variability of test results | 28 |
| Annex F (normative) Test method for flame spread of plastic piping | 31 |
| Bibliography | 33 |