

DIN V 18599-3:2007-02 (E)

Energy efficiency of buildings - Calculation of the net, final and primary energy demand for heating, cooling, ventilation, domestic hot water and lighting - Part 3: Net energy demand for air conditioning

Contents		Page
Foreword		4
Introduction		6
1	Scope	7
2	Normative references	9
3	Terms and definitions, symbols and units	10
3.1	Terms and definitions	10
3.2	Symbols, units and subscripts	13
4	Calculation methods	18
4.1	Characteristic value method	18
4.2	Special system designs	18
5	Use of balance parameters in other calculations	19
5.1	General considerations	19
5.2	Supply air volume flow of constant air volume systems	19
5.3	Supply air volume flow of systems with time-dependent or usage-dependent volume flow control	19
5.4	Supply air volume flow of systems with control of the volume flow as a function of the cooling load	20
5.5	Monthly mean supply air temperatures	22
6	Calculation of the delivered energy for air transport	23
6.1	Constant air volume systems	23
6.2	Variable air volume systems	24
6.2.1	Calculation principles	24
6.2.2	Systems with time-dependent or usage-dependent control of the volume flow	26
6.2.3	Systems with control of the volume flow as a function of the cooling load	26
7	Calculation of the energy needs for heating, cooling, humidification and dehumidification	27
7.1	Selecting a type of system	27
7.2	Conversion of energy characteristic values for freely-selected operating times and supply air temperatures	31
7.3	Conversion of energy characteristic values for systems with freely-selectable recovered heat coefficients	34
7.4	Denormalizing the energy characteristic values	35
8	Maximum power values	35
8.1	Design parameters for specific external air and extract air conditions	35
8.2	Determination of the enthalpy of supply air	37
8.3	Maximum heating power	39
8.4	Maximum cooling power	40
8.5	Maximum power for steam generation	41
Annex A (normative)	Energy characteristic values for thermal conditioning of air	42

A.1	General	42
Annex B (normative) Component usage times		45
B.1	General	45
Annex C (normative) Method and boundary conditions for determining the energy need for thermal air conditioning		45
C.1	General	45
C.2	Method and boundary conditions	45
Annex D (informative) System types, schematic diagrams		45
D.1	General	45
-- Prestandard -- Figures Page Figure 3 -- Sections of ventilation ductwork with constant resistance and with variable resistance		24
Figure 4 -- Correction factors to account for the daily operating time of a VAC system		34
Tables Table 1 -- Symbols		13
Table 2 -- Subscripts		17
Table 3 -- Monthly mean supply air temperature for ventilation systems without a cooling function		22
Table 4 -- Monthly mean supply air temperature for ventilation systems with neither reheating nor cooling functions		23
Table 5 -- Variant numbers of VAC systems in connection with the energy characteristic values according to Annex A		30
Table 6 -- Design parameters for specific external air conditions		35
Table 7 -- Design parameters for extract air conditions in the zone		36
Table A.1 -- Specific energy characteristic values for a whole year		42
Table A.2 -- Specific energy characteristic values for the month of January		45
Table A.3 -- Specific energy characteristic values for the month of February		45
Table A.4 -- Specific energy characteristic values for the month of March		45
Table A.5 -- Specific energy characteristic values for the month of April		45
Table A.6 -- Specific energy characteristic values for the month of May		45
Table A.7 -- Specific energy characteristic values for the month of June		45
Table A.8 -- Specific energy characteristic values for the month of July		45
Table A.9 -- Specific energy characteristic values for the month of August		45
Table A.10 -- Specific energy characteristic values for the month of September		45
Table A.11 -- Specific energy characteristic values for the month of October		45
Table A.12 -- Specific energy characteristic values for the month of November		45

Table A.13 -- Specific energy characteristic values for the month of December	45
Table B.1 -- Annual relative component usage times $t_{i,14^{\circ}\text{C},12\text{h}}$ for $t_{v,\text{mech}} = 12 \text{ h}$ and $V_{,\text{mech}} = 14$ $^{\circ}\text{C}$	45
Table B.2 -- Annual relative component usage times $t_{i,r,22^{\circ}\text{C},12\text{h}}$ for $t_{v,\text{mech}} = 12 \text{ h}$ and $V_{,\text{mech}} =$ $22 \text{ }^{\circ}\text{C}$	45
Table C.1 -- Default supply air humidity values	45
Table C.2 -- Default zone extract air temperature values	45
Table D.1 -- Schematic diagrams of system designs	45