

# DIN V 18599-5:2007-02 (E)

## Energy efficiency of buildings - Calculation of the net, final and primary energy demand for heating, cooling, ventilation, domestic hot water and lighting - Part 5: Final energy demand of heating systems

---

<b>Contents</b>		<b>Page</b>
Foreword .....		7
Introduction .....		9
<b>1</b>	<b>Scope .....</b>	<b>10</b>
<b>2</b>	<b>Normative references .....</b>	<b>11</b>
<b>3</b>	<b>Terms and definitions, symbols and units .....</b>	<b>13</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>13</b>
<b>3.2</b>	<b>Symbols, units and subscripts .....</b>	<b>17</b>
<b>4.2.1</b>	<b>Generator heat output .....</b>	<b>23</b>
<b>4.2.2</b>	<b>Delivered heat .....</b>	<b>24</b>
<b>4.2.3</b>	<b>Auxiliary energy .....</b>	<b>25</b>
<b>4.2.4</b>	<b>Uncontrolled heat gains due to the heating system .....</b>	<b>25</b>
<b>5</b>	<b>Boundary conditions for the individual subsystems .....</b>	<b>26</b>
<b>5.1</b>	<b>Part load levels .....</b>	<b>26</b>
<b>5.1.1</b>	<b>Heat control and emission .....</b>	<b>26</b>
<b>5.1.2</b>	<b>Heat distribution .....</b>	<b>26</b>
<b>5.1.3</b>	<b>Storage .....</b>	<b>26</b>
<b>5.1.4</b>	<b>Heat generation .....</b>	<b>27</b>
<b>5.2</b>	<b>Temperatures .....</b>	<b>27</b>
<b>5.3</b>	<b>Boiler rated output .....</b>	<b>29</b>
<b>5.4</b>	<b>Times .....</b>	<b>29</b>
<b>5.4.1</b>	<b>Running times .....</b>	<b>29</b>
<b>5.4.2</b>	<b>Distribution of annual values over individual months .....</b>	<b>32</b>
<b>6</b>	<b>Determination of energy expenditure .....</b>	<b>32</b>
<b>6.1</b>	<b>Heat control and emission .....</b>	<b>32</b>
<b>6.1.1</b>	<b>Efficiencies for free emitters (radiators); room heights 4 m .....</b>	<b>33</b>
<b>6.1.2</b>	<b>Efficiencies for water based embedded systems (surface heating); room heights 4 m .....</b>	<b>35</b>
<b>6.1.3</b>	<b>Efficiencies for electric heating; (room heights 4 m) .....</b>	<b>36</b>
<b>6.1.4</b>	<b>Efficiencies for air heating/residential ventilation; room heights 4 m .....</b>	<b>36</b>
<b>6.1.5</b>	<b>Efficiencies for air heating (HVAC systems); room heights 4 m .....</b>	<b>37</b>
<b>6.1.6</b>	<b>Efficiencies for rooms with heights 4 m (large indoor spaces) .....</b>	<b>37</b>
<b>6.1.7</b>	<b>Efficiencies for rooms with heights &gt; 10 m .....</b>	<b>39</b>
<b>6.1.8</b>	<b>Auxiliary energy <math>Q_{h,ce,aux}</math> .....</b>	<b>40</b>
<b>6.2</b>	<b>Heat distribution <math>Q_{h,d}</math> - central hot water heating pipe system .....</b>	<b>43</b>
<b>6.2.1</b>	<b>Auxiliary energy for central hot water heating pipe system .....</b>	<b>45</b>
<b>6.3</b>	<b>Storage .....</b>	<b>50</b>
<b>6.4</b>	<b>Heat generator .....</b>	<b>52</b>
<b>6.4.1</b>	<b>Solar systems supporting domestic hot water heating and space heating systems (combination systems) .....</b>	<b>53</b>
<b>6.4.1.1</b>	<b>Satisfaction of energy need by solar combination systems .....</b>	<b>53</b>
<b>6.4.1.2</b>	<b>Energy contribution of solar combination systems .....</b>	<b>53</b>
-- Prestandard --	<b>6.4.1.3 Calculation procedure for combination systems .....</b>	<b>56</b>

6.4.1.4	Calculation procedure for large combination systems .....	60
6.4.1.5	Auxiliary energy for operation of the solar pump .....	60
6.4.2	Heat pump .....	61
6.4.2.1	Principles of the calculation .....	62
6.4.2.2	Outdoor air as heat source; average climatic data for Germany .....	65
6.4.2.3	Energy need for domestic hot water .....	69
6.4.2.4	Calculation of the fraction of heating energy to be provided by the second generator (back-up heating) .....	69
6.4.2.5	Heat output and coefficient of performance of the heat pump at full load (steady-state operation) .....	73
6.4.2.6	Coefficient of performance in part load operation .....	76
6.4.2.7	Generator thermal losses .....	78
6.4.2.8	Calculation of total energy consumption .....	79
6.4.2.9	Auxiliary energy .....	80
6.4.2.10	Energy consumption of the second generator (back-up heating system) .....	81
6.4.2.11	Total energy consumption .....	82
6.4.2.12	Regenerative energy contribution .....	82
6.4.2.13	Performance factor to account for the generator subsystem .....	82
6.4.3	Conventional boilers .....	83
6.4.3.1	Multiple boiler systems .....	83
6.4.3.2	Fuel-fired systems (boilers) .....	84
6.4.3.3	Hand stocked biomass combustion systems .....	94
6.4.3.4	Decentralized fuel-fired systems .....	99
6.4.4	Electric heaters .....	101
6.4.4.1	Decentralized electric heaters .....	101
6.4.4.2	Central electric heaters .....	101
6.4.5	District heating and local heating .....	101
6.4.6	Decentralized CHP .....	102
<b>Annex A (normative) Energy use to meet the heating need .....</b>		<b>103</b>
A.1	Electrically driven heat pumps .....	103
A.2	Heat pumps with combustion drive .....	104
A.3	Default values for heat pump calculations .....	105
A.3.1	Default power values and coefficients of performance for electrically driven heat pumps	105
A.4	Default power values and coefficients of performance for combustion engine-driven heat pumps .....	106
A.4.1	Air-to-water heat pumps .....	106
A.4.2	Combustion engine-driven air-to-water heat pumps .....	107
A.4.3	Air-to-air heat pumps .....	107
A.4.4	Absorption heat pumps .....	108
A.5	Correction factor for part load operation .....	110
A.5.1	Electrically driven heat pumps .....	110
A.5.2	Absorption heat pumps with modulation burner .....	111
A.6	Calculation procedure for source and sink temperature corrections with a set exergetic efficiency .....	111
A.7	VRF systems: relative heat output performance .....	113
<b>Annex B (informative) Dimensioning of buildings .....</b>		<b>116</b>
B.1	General information .....	116
<b>Bibliography .....</b>		<b>119</b>
<b>-- Prestandard -- Figures Figure 3 -- Subscript system .....</b>		<b>20</b>
<b>Figure 4 -- Designation of pipes in hot water heating pipe systems .....</b>		<b>44</b>
<b>Figure 5 -- Distribution of cumulated bin hours for the outdoor air temperature .....</b>		<b>63</b>
<b>Figure 6 -- Bin hours and energy fractions of the heat pump and the second generator (back-up heating) in alternate operation .....</b>		<b>70</b>

Figure 7 -- Bin hours and energy fractions of the heat pump and the second generator (back-up heating) in parallel operation .....	71
Figure 8 -- Bin hours and energy fractions of the heat pump and the second generator (back-up heating) in partly parallel operation .....	72
Figure A.1 -- Energy balance of the generator subsystem (electrically driven heat pump) .....	103
Figure A.2 -- Energy balance of the generator subsystem (heat pump with combustion drive) .....	104
Figure A.3 -- Heat output of combustion engine-driven air-to-water heat pumps at various source and sink temperatures .....	106
Figure A.4 -- Standard coefficients of performance for combustion engine-driven air-to-water heat pumps at various source and sink temperatures .....	107
Figure A.5 -- Heat output of combustion engine-driven air-to-air heat pumps .....	107
Figure A.6 -- Standard coefficient of performance of combustion engine-driven air-to-air heat pumps .....	108
Figure A.7 -- Heat output of water-to-water NH <sub>3</sub> /H <sub>2</sub> O absorption heat pumps at various source and sink temperatures .....	108
Figure A.8 -- Heat output of water-to-water H <sub>2</sub> O/LiBr absorption heat pumps at various source and sink temperatures .....	109
Figure A.9 -- VRF systems: COP heating for load ratios between 10 % and 100 % .....	114
Figure A.10 -- VRF systems: relative heat output performance .....	114
Figure A.11 -- VRF systems: relative COP heating for load ratios between 10 % and 100 % .....	115
Figure B.1 -- Building geometry .....	116
Tables Table 1 -- Symbols and units .....	17
Table 2 -- Subscripts .....	19
Table 3 -- Input parameters .....	21
Table 4 -- Output parameters .....	23
Table 5 -- Design temperatures .....	28
Table 6 -- Efficiencies for free emitters (radiators); room heights 4 m .....	34
Table 7 -- Efficiencies for water based embedded systems (surface heating); room heights 4 m .....	35
Table 8 -- Efficiencies for electric heating; (room heights 4 m) .....	36
Table 9 -- Efficiencies for air heating (HVAC systems) for room heights 4 m .....	37
-- Prestandard -- Table 10 -- Efficiencies for rooms with heights from 4 m to 10 m .....	38
Table 11 -- Efficiencies for rooms with heights > 10 m .....	39
Table 12 -- Default values for auxiliary energy for the control system .....	41
Table 13 -- Default values for the auxiliary energy of fans for air supply in rooms where h 4 m .....	41

Table 14 -- Default values for the auxiliary energy of fans and for the control system in rooms $h > 4$ m in height (large indoor spaces) .....	42
Table 15 -- Default values .....	44
Table 16 -- Assumptions for heat transfer coefficients $U_i$ in $W/(m \cdot K)$ .....	45
Table 17 -- Constants CP1,CP2 for calculation of the expenditure factor of heat pumps .....	49
Table 18 -- Distribution of annual solar contribution over months .....	56
Table 19 -- Correction factor for inclination and alignment .....	57
Table 20 -- Correction factor for the solar load ratio (fslr) .....	58
Table 21 -- Correction factor for the heat loss rate of the storage tank or tanks (fs,loss) .....	58
Table 22 -- Correction factor for the temperature level of the space heating $f_{h,T}$ .....	59
Table 23 -- Energy fraction from the combination system for domestic water heating .....	60
Table 24 -- Hours frequency of outdoor temperature (reference location: Würzburg) .....	66
Table 25 -- Monthly hours sum in the individual bins, distributed according to the testing points from DIN EN 14511 (all parts) .....	69
Table 26 -- Mean source temperature for ground and groundwater as a function of the average outdoor temperature .....	74
Table 27 -- Mean source temperature for ground and groundwater as a function of the average monthly outdoor temperature .....	74
Table 28 -- Correction factors $f$ to account for deviations in temperature differences in heat pump measurement and operation .....	75
Table 29 -- Boiler temperatures .....	87
Table 30 -- Temperature correction factors .....	87
Table 31 -- Efficiency factors .....	90
Table 32 -- Radiation loss factors .....	91
Table 33 -- Stand-by heat factors .....	92
Table 34 -- Auxiliary energy factors .....	93
Table 35 -- Default values .....	99
Table 36 -- Efficiency factor .....	100
Table 37 -- DDS as a function of the primary temperature and type of dwelling substation .....	102
Table 38 -- Coefficient BDS as a function of the class of insulation and the type of dwelling substation .....	102
Table A.1 -- Air-to-water heat pumps with a supply temperature of $35\text{ °C}$ .....	105
Table A.2 -- Air-to-water heat pumps with a supply temperature of $50\text{ °C}$ .....	105
Table A.3 -- Brine-to-water heat pumps with supply temperatures of $35\text{ °C}$ and $50\text{ °C}$ .....	105

**Table A.4 -- Water-to-water heat pumps with supply temperatures of 35 °C and 50 °C ..... 106**

**Table A.5 -- Correction factor for part load operation of electrically driven heat pumps with radiators ..... 110**

**-- Prestandard -- Table A.6 -- Correction factor for part load operation of electrically driven heat pumps with surface heating systems ..... 110**

**Table A.7 -- Correction factor for part load operation of absorption heat pumps ..... 111**

**Table A.8 -- Relative heat output performance ..... 113**