

DIN V 18599-4:2007-02 (E)

Energy efficiency of buildings - Calculation of the net, final and primary energy demand for heating, cooling, ventilation, domestic hot water and lighting - Part 4: Net and final energy demand for lighting

Contents		Page
Foreword		5
Introduction		7
1	Scope	8
2	Normative references	9
3	Terms and definitions, symbols and units	10
3.1	Terms and definitions	10
3.2	Symbols, units and subscripts	13
3.2.1	Symbols and units	13
3.2.2	Subscripts	13
5	Calculations	15
5.1	Principle of the balance calculations	15
5.2	Subdivision of a building zone	17
5.2.1	Subdivision into evaluation areas	17
5.2.2	Daylight area	18
5.3	Operating times	19
5.4	Artificial lighting	19
5.4.1	Tabular method	19
5.4.2	Simplified utilization factor method	22
5.4.3	Detailed engineering planning	23
5.4.4	Determination of the specific electrical evaluation power in existing buildings	23
5.5	Daylight	24
5.5.1	Annual daylight supply with vertical façades	26
5.5.2	Annual daylight supply through rooflights	37
5.5.3	Daylight-responsive control systems	44
5.5.4	Monthly evaluation method	45
5.6	Occupancy (presence)	46
Annex A (normative)	Reduction factor k_A to take into account the relative proportion of the area needed for the visual task	48
A.1	General	48
A.2	Detailed calculation of $CTL_{Vers,Sa,j}$	49
A.3	Examples of the electrical evaluation power of various illumination solutions	56
A.3.1	General	56
A.3.2	Personal offices (single occupant)	57
A.3.3	Office for two occupants	60
A.3.4	Workgroup offices	63
A.3.5	Call centres (landscaped offices)	66
A.3.6	Corridors	70
A.3.7	Production hall	72
A.4	Example: Determination of the daylight supply factor $CTL_{Vers,j}$ for a space with rooflights	74
A.4.1	General	74
A.4.2	Determination of the electrical evaluation power	74

A.4.3	Determination of the daylight supply factor CTL_{Vers}	75
A.4.4	Determination of the annual and monthly energy use for lighting	76
	Bibliography	79
--	Prestandard -- Figures Figure 3 -- Flowchart showing calculation of the energy need for lighting .	17
Figure 4	-- Determination of height $h'R$ (schematic diagram)	21
Figure 5	-- Three-stage approach for determining the daylight supply factor $CTL_{Vers,j}$	25
Figure 6	-- Effect of the angle of elevation of a linear obstruction V,IV (schematic diagram)	27
Figure 7	-- Effect of the horizontal obstruction angle due to an overhang V,hA (schematic diagram)	27
Figure 8	-- Effect of the vertical obstruction angle V,vA due to a side fin (schematic diagram)	28
Figure 9	-- Geometrical parameters used to define the well index w_i (notation)	29
Figure 10	-- Example of a set of functions to determine the daylight supply factor $CTL_{Vers,SNA,j}$ as a function of DR_b and $eff_{SNA,j}$ according to equation (28) for $mE = 500$ lx and a south-facing façade	36
Figure 11	-- Notation used to describe the geometry of the upstands of spaces with dome lights and continuous rooflights	40
Figure 12	-- Notation used to describe the geometry of rooflights in sawtooth roofs (sheds)	40
Figure A.1	-- Task area AS and immediate surrounding area AU (schematic diagram)	49
Figure A.2	-- Effective light transmittances $eff_{u,SA}$ into the lower quarter-space and $eff_{o,SA}$ into the upper quarter-space (schematic diagram)	53
Figure A.3	-- Factor $C'TL_{Vers,SA}$ for areas with activated solar radiation protection and/or glare protection as a function of the total light transmittance eff_{SA} and the distribution key factor v_{SA} for $mE = 500$ lx	55
Figure A.4	-- Daylight supply factor $CTL_{Vers,SA}$ for areas with activated solar radiation protection and/or glare protection as a function of the factor $C'TL_{Vers,SA}$ and the daylight factor DR_b of the building carcass roof opening	56
Figure A.5	-- Personal office - illumination solution 1	57
Figure A.6	-- Personal office - illumination solution 2	58
Figure A.7	-- Personal office - illumination solution 3	59
Figure A.8	-- Office for two occupants -- illumination solution 1	60
Figure A.9	-- Office for two occupants - illumination solution 2	61
Figure A.10	-- Office for two occupants - illumination solution 3	62
Figure A.11	-- Workgroup office - illumination solution 1	63
Figure A.12	-- Workgroup office - illumination solution 2	64
Figure A.13	-- Call centre - illumination solution 1	66
Figure A.14	-- Call centre - illumination solution 2	68
Figure A.15	-- Corridor - illumination solution 1	70

Figure A.16 -- Corridor - illumination solution 2	71
Figure A.17 -- Production hall - illumination solution 1	72
Figure A.18 -- Production hall - illumination solution 2	73
Figure A.19 -- Rooflights	74
-- Prestandard -- Tables Table 1 -- Calculation values of the specific electrical evaluation power $p_{j,lx}$ in relation to the floor area per lx of maintained illuminance at the work plane, for luminaires with tubular fluorescent lamps and electronic ballast (EB)	20
Table 2 -- Correction factor k_L to account for different types of lamp, with reference to Table 1	21
Table 3 -- Correction factor k_R to account for the effect of the space geometry in relation to the room index k	22
Table 4 -- Utilization factors R as a function of the illumination type and the room index	23
Table 5 -- Factor k_{BG} for determining the power of a system from the power consumption of lamps	24
Table 6 -- Daylight supply classification as a function of the daylight factor $DR_{b,j}$ of the building carcass opening	30
Table 7 -- Relative times $t_{rel,TL,SNA,j}$ and $t_{rel,TL,SA,j}$ for de-activated and activated solar radiation and/or glare protection systems, as a function of the façade orientation	31
Table 8 -- Typical values of light transmittance $D_{65,SNA}$ of transparent building components	33
Table 9 -- Daylight supply factor $CTL,Vers,SNA,j$ as a function of the effective light transmittance of the façade, daylight supply factor, maintained illuminance and façade orientation	34
Table 10 -- Parameters a_1 und a_2 to be used in equation (28), as a function of the maintained illuminance mE	35
Table 11 -- Parameter a_3 to be used in equation (28) to account for the façade orientation	35
Table 12 -- System solutions (to be applied for the period $t_{rel,TL,SA,j}$)	36
Table 13 -- Typical values of light transmittance D_{65}, U and g of components frequently used in rooflight construction	38
Table 14 -- External daylight factor Da as a function of the façade slope F for a floor reflectance B of 0,2 (without taking obstruction into account)	40
Table 15 -- Dome light utilization factors R , as a function of the room index k and the geometry parameters of the upstand design	41
Table 16 -- Utilization factors R of rooflights in sawtooth roofs (sheds), as a function of the room index and the geometry parameters	42
Table 17 -- Classification of daylight supply as a function of the daylight factor jD	43
Table 18 -- Daylight supply factor $CTL,Vers,j$ of spaces with rooflights as a function of the daylight supply classification and the maintained illuminance for façades with different orientations and slopes	43
Table 19 -- Correction factor CTL,kon,j to account for the effect of daylight-responsive control systems in a zone n , as a function of the maintained illuminance mE and the daylight supply classification	45

Table 20 -- Monthly distribution key factors $v_{\text{Monat},i}$ for vertical façades	46
Table 21 -- Monthly distribution key factors $v_{\text{Monat},i}$ for rooflights	46
Table 22 -- Factor $C_{\text{Prä},\text{kon},j}$ to account for the efficiency of presence detection systems	47
Table A.1 --Typical effective light transmittance eff_{SA} of various types of solar radiation protection and/or Table A.2 -- Typical values of the distribution key factor $V_{\text{SA},j}$ for various types of façade components	53
Table A.3 -- Monthly energy use for continuous-type rooflights	78
Table A.4 -- Monthly energy use for shed rooflights	78