DIN EN 14934:2007-12 (E)

Thermal insulation and light weight fill products for civil engineering applications - Factory made products of ex truded polystyrene foam (XPS) - Specification

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms, definitions, symbols, units and abbreviated terms 6
3.1 Terms and definitions 6
3.2 Symbols, units and abbreviated terms 7

4 Requirements 9
4.1 General 9
4.2 For all applications 9
4.3 For specific applications 11

5 Test methods 17
5.1 Sampling 17
5.2 Conditioning 17
5.3 Testing 17

6 Designation code 20

7 Evaluation of conformity 21

8 Marking and labelling 22

Annex A (normative) Determination of the declared values of thermal resistance and thermal conductivity 23

A.1 Introduction 23
A.2 Input data 23
A.3 Declared values 23

Annex B (normative) Factory Production Control 25

Annex C (normative) Determination of the aged values of thermal resistance and thermal conductivity 29

C.1 Scope 29
C.2 Procedure for XPS foam without diffusion tight laminates 29
C.3 Procedure for XPS foam for use with diffusion tight facings on both sides 30
C.4 Calculation of aged value 31
C.5 Blowing agent 32
C.6 Product grouping 32

Annex D (normative) Determination of behaviour under cyclic square wave load 33

D.1 Scope 33
D.2 Definitions 33
D.3 Principle 34
D.4 Testing equipment 34

D.5 Test specimens 35
D.6 Procedure 35
D.7 Calculation and expression of results 37
D.8 Accuracy of measurement 38
D.9 Test report 38

Annex E (informative) Additional properties 39

E.1 General 39
E.2 Compressive modulus of elasticity 39
E.3 Determination of volume percentage of open and closed cells 39
E.4 Determination of shear strength 39

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/106/EEC, EU Construction Products Directive 41

ZA.1 Scope and relevant characteristics 41

ZA.2 Procedures for the attestation of conformity of extruded polystyrene foam products 43

ZA.3 CE Marking and labelling 48

Bibliography 50

Figures Figure D.1 -- Required load cycle during the fatigue test 35

Figure D.2 -- Dimensions of the test specimen 36

Figure D.3 -- Test set-up 37

Figure ZA.1 -- Example CE marking information 49

Tables Table 1 -- Tolerances of length, width, squareness and flatness 10

Table 2 -- Classes for thickness tolerances 10

Table 3 -- Levels for compressive stress at 10 % deformation or compressive strength 11

Table 4 -- Levels for deformation under specified compressive load and temperature conditions 12

Table 5 -- Levels for compressive stress at 2 % deformation or compressive strength 13

Table 6 -- Levels for compressive stress at 5 % deformation or compressive strength 13

Table 7 -- Levels for long term water absorption by total immersion 16

Table 8 -- Levels for long term water absorption by diffusion 16

Table 9 -- Levels for Freeze-thaw resistance 16

Table 10 -- Test methods, test specimens and conditions 18

Table A.1 -- Values of k for one sided 90 % tolerance interval with a confidence level of 90 % 24

Table B.1 -- Minimum product testing frequencies 25

Table B.2 -- Minimum product testing frequencies for the reaction to fire characteristics 27

Table E.1 -- Test methods, test specimens, conditions and minimum testing frequencies 40

Table ZA.1 -- Relevant clauses 42

Table ZA.2 -- System(s) of attestation of conformity 44

Table ZA.2.1 -- A ssignment of evaluation of conformity tasks for products under system 1 45

Table ZA.2.2 -- Assignment of evaluation of conformity tasks for products under system 3 and 3 (with 4 for RtF) 46