

DIN EN 12899-1:2008-02 (E)

Fixed, vertical road traffic signs - Part 1: Fixed signs

| Contents | | Page |
|--|---|-------------|
| Foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms, definitions, symbols and abbreviations | 7 |
| 4 | Retroreflective sign face material | 8 |
| 4.1 | Glass bead material | 8 |
| 4.2 | Microprismatic material | 12 |
| 5 | Structural performance | 12 |
| 5.1 | General | 12 |
| 5.2 | Partial safety factors | 14 |
| 5.3 | Loads | 14 |
| 5.4 | Deflections | 16 |
| 6 | Supports | 20 |
| 6.1 | Tops | 20 |
| 6.2 | Base compartments | 20 |
| 6.3 | Performance under vehicle impact | 20 |
| 6.4 | Corrosion resistance | 21 |
| 6.5 | Base plates | 21 |
| 7 | Sign plates, sign faces, transilluminated signs, externally illuminated signs and supports | 21 |
| 7.1 | Design | 21 |
| 7.2 | Sign faces | 24 |
| 7.3 | Transilluminated signs | 25 |
| 7.4 | Externally illuminated signs | 28 |
| 8 | Sign assemblies | 30 |
| 9 | Marking, labelling and product information | 30 |
| 9.1 | General | 30 |
| 9.2 | Marking and labelling | 30 |
| 9.3 | Product information | 30 |
| 9.4 | Luminaires | 31 |
| 10 | Evaluation of conformity | 31 |
| 11 | Dangerous substances | 31 |
| A.1 | Wind load | 32 |
| A.2 | Snow clearance, dynamic load, load combination | 41 |
| Annex A (normative) Test points for horizontal and vertical loads | | 32 |
| EU Construction Products Directive | | 44 |

| | |
|--|-----------|
| ZA.1 Scope and relevant characteristics | 44 |
| ZA.2 Procedure for attestation of conformity of fixed vertical road traffic signs | 51 |
| ZA.3 CE marking and labelling | 52 |