

# DIN CEN/TS 14826:2004-10 (E)

Postal services - Automatic identification of items - Two dimensional bar code symbol print quality specification for machine readable Digital Postage Marks; English version CEN/TS 14826:2004

---

Inhalt	Seite
Foreword .....	4
Introduction.....	5
1 Scope.....	7
2 Normative references.....	7
3 Terms and definitions .....	7
4 Symbols and abbreviations.....	8
5 Requirements.....	9
6 Basic measurement methodology .....	10
7 Verification requirements for Digital Postage Marks.....	11
7.1 Verification equipment.....	11
7.2 Optical geometry .....	11
7.3 Light source .....	11
7.4 Measuring aperture .....	12
7.4.1 Measuring aperture for two-dimensional multi-row symbologies .....	12
7.4.2 Measuring aperture for two-dimensional matrix symbologies.....	13
7.5 Mail format .....	13
8 Grading implications for individual symbol attributes.....	13
9 Additional grading parameters - Quiet zone .....	15
10 Qualification of printing systems for Digital Postage Marks.....	15
Annex A (normative) Test procedure for printing systems for Digital Postage Marks .....	16
A.1 Environmental conditions for test.....	16
A.2 Test materials .....	16
A.3 Test procedure.....	17
Annex B (informative) Light sources and spectral response characteristics for verification of Digital Postage Marks .....	18
B.1 Narrow-band illumination .....	18
B.2 Broad-band illumination (white light).....	18
B.2.1 General .....	18
B.2.2 Halogen lamps.....	19
B.2.3 Light emitting diode .....	19
B.2.4 Gas discharge lamp .....	19
B.2.5 Fluorescent lamps.....	20
Annex C (informative) Symbol parameters measured in accordance with ISO/IEC 15415 .....	21
C.1 Parameters for two-dimensional multi-row symbols.....	21
C.2 Parameters for two-dimensional matrix symbologies.....	22
Annex D (informative) Characteristics of Digital Postage Mark printing and reading environments that affect print quality.....	23
D.1 Printing of Digital Postage Marks .....	23
D.1.1 Ink-jet printing.....	23
D.1.2 Laser printing.....	23
D.1.3 Thermal transfer printing.....	24
D.1.4 Direct thermal printing.....	24

D.1.5	Matching X dimension to printer resolution .....	24
D.2	Reading environment .....	25

**Annex E (informative) Possible causes of low parameter grades in the Digital Postage Mark**

	environment .....	26
E.1	Multi-row symbologies .....	26
E.1.1	Symbol Contrast .....	26
E.1.2	Minimum reflectance .....	26
E.1.3	Minimum edge contrast .....	26
E.1.4	Modulation .....	26
E.1.5	Decode .....	27
E.1.6	Defects .....	27
E.1.7	Decodability .....	27
E.1.8	Codeword yield .....	27
E.1.9	Unused error correction (UEC) .....	27
E.1.10	Quiet zone .....	27
E.1.11	Print growth .....	28
E.1.12	Codeword quality .....	28
E.2	Matrix symbologies .....	28
E.2.1	Symbol Contrast .....	28
E.2.2	Fixed pattern damage .....	28
E.2.3	Modulation .....	28
E.2.4	Axial non-uniformity .....	29
E.2.5	Grid non-uniformity .....	29
E.2.6	Unused error correction .....	29
E.2.7	Quiet zone .....	29
E.2.8	Print growth .....	29
	Bibliography .....	30