

# ISO 6533:2012-09 (E)

## Forestry machinery - Portable chain-saw front hand-guard - Dimensions and clearances

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative reference</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>General</b> .....	<b>2</b>
<b>5</b>	<b>Gauge dimensions</b> .....	<b>2</b>
<b>6</b>	<b>Determination of reference point <math>X_0</math></b> .....	<b>2</b>
<b>7</b>	<b>Front hand-guard dimensions</b> .....	<b>5</b>
7.1	Front hand-guard width, $W_1$ .....	5
7.2	Front hand-guard height over front handle, $H_1$ and $H_{1A}$ .....	5
7.3	Line between $X_0$ and the rearmost part of unprotected saw chain .....	6
7.4	Front hand-guard openings, $H_3$ .....	6
<b>8</b>	<b>Clearance between the hand-guard and the chain saw body, <math>H_2</math></b> .....	<b>7</b>
<b>9</b>	<b>Clearances between the hand-guard and the front handle</b> .....	<b>7</b>







