

# ISO 22884:2004-04 (E)

## Castors and wheels - Requirements for applications over 1,1 m/s (4 km/h) and up to 4,4 m/s (16 km/h)

---

| <b>Contents</b> |                                                                                 | <b>Page</b> |
|-----------------|---------------------------------------------------------------------------------|-------------|
| <b>1</b>        | <b>Scope .....</b>                                                              | <b>1</b>    |
| <b>2</b>        | <b>Normative references .....</b>                                               | <b>1</b>    |
| <b>3</b>        | <b>Terms and definitions .....</b>                                              | <b>1</b>    |
| <b>4</b>        | <b>Classification, characteristics and dimensions .....</b>                     | <b>1</b>    |
| <b>4.1</b>      | <b>Classification .....</b>                                                     | <b>1</b>    |
| <b>4.2</b>      | <b>Characteristics .....</b>                                                    | <b>1</b>    |
| <b>4.3</b>      | <b>Top plate .....</b>                                                          | <b>2</b>    |
| <b>4.4</b>      | <b>Offset .....</b>                                                             | <b>3</b>    |
| <b>4.5</b>      | <b>Wheel .....</b>                                                              | <b>3</b>    |
| <b>4.6</b>      | <b>Load capacity .....</b>                                                      | <b>6</b>    |
| <b>5</b>        | <b>Requirements for testing .....</b>                                           | <b>6</b>    |
| <b>5.1</b>      | <b>General .....</b>                                                            | <b>6</b>    |
| <b>5.2</b>      | <b>Standard conditions .....</b>                                                | <b>6</b>    |
| <b>5.3</b>      | <b>Initial wheel play .....</b>                                                 | <b>7</b>    |
| <b>5.4</b>      | <b>Initial swivel play .....</b>                                                | <b>7</b>    |
| <b>5.5</b>      | <b>Electrical resistance test .....</b>                                         | <b>8</b>    |
| <b>5.6</b>      | <b>Fatigue test for braking and/or locking device .....</b>                     | <b>8</b>    |
| <b>5.7</b>      | <b>Efficiency check of wheel braking and/or locking device .....</b>            | <b>9</b>    |
| <b>5.8</b>      | <b>Efficiency check of swivel braking and/or locking device .....</b>           | <b>10</b>   |
| <b>5.9</b>      | <b>Static test .....</b>                                                        | <b>10</b>   |
| <b>5.10</b>     | <b>Dynamic test .....</b>                                                       | <b>10</b>   |
| <b>5.11</b>     | <b>Efficiency check of wheel braking and/or locking device .....</b>            | <b>12</b>   |
| <b>5.12</b>     | <b>Efficiency check of swivel braking and/or locking device .....</b>           | <b>12</b>   |
| <b>5.13</b>     | <b>Final wheel play .....</b>                                                   | <b>12</b>   |
| <b>5.14</b>     | <b>Final swivel play .....</b>                                                  | <b>12</b>   |
| <b>6</b>        | <b>Conformity .....</b>                                                         | <b>12</b>   |
| <b>7</b>        | <b>Marking of the product .....</b>                                             | <b>13</b>   |
| <b>7.1</b>      | <b>Product marking .....</b>                                                    | <b>13</b>   |
| <b>7.2</b>      | <b>Marking of electrically conductive or antistatic castors or wheels .....</b> | <b>13</b>   |
|                 | <b>Bibliography .....</b>                                                       | <b>14</b>   |