

# ISO 22881:2004-07 (E)

## Castors and wheels - Requirements for use on manually propelled equipment for institutional applications

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Dimensions and classification .....</b>	<b>1</b>
<b>4.1</b>	<b>Characteristics .....</b>	<b>1</b>
<b>4.2</b>	<b>Fixing system .....</b>	<b>1</b>
<b>4.3</b>	<b>Offset .....</b>	<b>6</b>
<b>4.4</b>	<b>Wheels .....</b>	<b>6</b>
<b>4.5</b>	<b>Load capacity .....</b>	<b>8</b>
<b>5</b>	<b>Requirements for testing .....</b>	<b>8</b>
<b>5.1</b>	<b>General .....</b>	<b>8</b>
<b>5.2</b>	<b>Standard conditions .....</b>	<b>8</b>
<b>5.3</b>	<b>Initial wheel play .....</b>	<b>8</b>
<b>5.4</b>	<b>Initial swivel play .....</b>	<b>10</b>
<b>5.5</b>	<b>Electrical resistance test .....</b>	<b>10</b>
<b>5.6</b>	<b>Fatigue test for braking and/or locking devices .....</b>	<b>11</b>
<b>5.7</b>	<b>Efficiency check of wheel braking and/or locking devices .....</b>	<b>12</b>
<b>5.8</b>	<b>Efficiency check of swivel braking and/or locking devices .....</b>	<b>12</b>
<b>5.9</b>	<b>Static test .....</b>	<b>13</b>
<b>5.10</b>	<b>Dynamic test .....</b>	<b>14</b>
<b>5.11</b>	<b>Efficiency check of wheel braking and/or locking devices .....</b>	<b>14</b>
<b>5.12</b>	<b>Efficiency check of swivel braking and/or locking devices .....</b>	<b>15</b>
<b>5.13</b>	<b>Final wheel play .....</b>	<b>15</b>
<b>5.14</b>	<b>Final swivel play .....</b>	<b>15</b>
<b>6</b>	<b>Conformity .....</b>	<b>15</b>
<b>7</b>	<b>Marking of the product .....</b>	<b>16</b>
<b>7.1</b>	<b>Product marking .....</b>	<b>16</b>
<b>7.2</b>	<b>Marking of electrically conductive or antistatic castors or wheels .....</b>	<b>16</b>
	<b>Bibliography .....</b>	<b>17</b>