

DIN EN ISO 9241-920:2016-09 (E)

Ergonomics of human-system interaction - Part 920: Guidance on tactile and haptic interactions (ISO 9241-920:2009)

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 5 |
| Foreword | | 6 |
| Introduction | | 8 |
| 1 | Scope | 9 |
| 2 | Applying ISO 9241-920 | 9 |
| 2.1 | Recommendations | 9 |
| 2.2 | Evaluation of products | 9 |
| 3 | Tactile/haptic inputs, outputs, and/or combinations | 10 |
| 3.1 | General guidance on tactile/haptic inputs, outputs and/or combinations | 10 |
| 3.1.1 | Optimizing performance | 10 |
| 3.1.2 | Providing accessible information on tactile/haptic elements | 10 |
| 3.1.3 | Providing contextual information | 10 |
| 3.1.4 | Using consistent labels | 10 |
| 3.1.5 | Identifying system state | 11 |
| 3.1.6 | Minimizing fatigue | 11 |
| 3.1.7 | Providing alternative input methods | 11 |
| 3.1.8 | Maintaining coherence between modalities | 11 |
| 3.1.9 | Combining modalities | 12 |
| 3.1.10 | Presenting realistic experiences | 12 |
| 3.1.11 | Isolation of individual interface elements | 12 |
| 3.2 | Intentional individualization | 13 |
| 3.2.1 | Enabling users to change modalities | 13 |
| 3.2.2 | Enabling force feedback override | 13 |
| 3.2.3 | Enabling users to individualise tactile parameters | 13 |
| 3.3 | Unintentional user perceptions | 13 |
| 3.3.1 | Limiting acoustic output of tactile/haptic display | 13 |
| 3.3.2 | Limiting heat gain of contact surface | 13 |
| 3.3.3 | Avoiding sensory adaptation | 14 |
| 3.3.4 | Recovering from sensory adaptation | 14 |
| 3.3.5 | Avoiding unintended perceptual illusions | 14 |
| 3.3.6 | Preventing temporal masking | 14 |
| 4 | Attributes of tactile and haptic encoding of information | 14 |
| 4.1 | High level guidance on tactile/haptic encoding of information | 14 |
| 4.1.1 | Using familiar tactile/haptic patterns | 14 |
| 4.1.2 | Making tactile/haptic encoding obvious | 14 |
| 4.1.3 | Conformity to user expectations | 15 |
| 4.1.4 | Using sensory substitution | 15 |
| 4.1.5 | Using appropriate spatial addressability and resolution | 15 |
| 4.1.6 | Using tactile apparent location | 15 |
| 4.1.7 | Using distal body parts for high spatial resolution | 15 |
| 4.1.8 | Using higher addressability for trained users | 15 |
| 4.1.9 | Using tactile apparent motion | 15 |
| 4.1.10 | Preventing spatial masking | 16 |
| 4.2 | Guidance on specific tactile/haptic attributes for encoding information | 16 |
| 4.2.1 | Selecting dimensions for encoding information | 16 |

| | | |
|-----------------------|---|----|
| 4.2.2 | Discriminating between attribute values | 17 |
| 4.2.3 | Limiting the number of attribute values | 17 |
| 4.2.4 | Combining properties | 17 |
| 4.2.5 | Limiting complexity | 17 |
| 4.2.6 | Encoding by object shape | 17 |
| 4.2.7 | Encoding information by temporal pattern | 17 |
| 4.2.8 | Encoding information using vibration amplitude | 17 |
| 4.2.9 | Encoding information by vibration frequency | 18 |
| 4.2.10 | Encoding by location | 18 |
| 4.2.11 | Encoding by temperature | 18 |
| 4.2.12 | Encoding by thermal conductivity | 18 |
| 4.2.13 | Identifying information values | 18 |
| 5 | Content-specific encoding | 19 |
| 5.1 | Encoding and text data | 19 |
| 5.2 | Encoding and using graphical data | 19 |
| 5.2.1 | Displaying tactile/haptic graphics | 19 |
| 5.2.2 | Using grids on tactile graphs | 19 |
| 5.2.3 | Using landmarks in tactile maps | 19 |
| 5.2.4 | Providing scales for tactile maps | 19 |
| 5.3 | Encoding and using controls | 20 |
| 5.3.1 | Using tactile/haptic controls | 20 |
| 5.3.2 | Using size and spacing of controls to avoid accidental activation | 20 |
| 5.3.3 | Avoiding difficult control actions | 20 |
| 5.3.4 | Using force to avoid accidental activation | 20 |
| 5.3.5 | Interacting with controls | 20 |
| 6 | Design of tactile/haptic objects and space | 21 |
| 6.1 | Tactile/haptic display spaces | 21 |
| 6.1.1 | Ease of perceiving multiple tactile/haptic objects | 21 |
| 6.1.2 | Ease of identifying adjacent tactile/haptic objects | 21 |
| 6.1.3 | Maintaining separation between surfaces of objects | 21 |
| 6.1.4 | Separating tactile/haptic elements | 22 |
| 6.1.5 | Avoiding empty spaces | 22 |
| 6.1.6 | Avoiding volume limits | 22 |
| 6.1.7 | Avoiding falling out of the tactile/haptic space | 22 |
| 6.2 | Objects | 22 |
| 6.2.1 | Using appropriate object size | 22 |
| 6.2.2 | Creating discriminable tactile/haptic symbols | 22 |
| 6.2.3 | Creating tactile/haptic symbols from visual symbols | 23 |
| 6.2.4 | Tactile/haptic object angles | 23 |
| 6.2.5 | Tactile/haptic object corners | 23 |
| 7 | Interaction | 23 |
| 7.1 | Navigating tactile/haptic space | 23 |
| 7.1.1 | Providing navigation information | 23 |
| 7.1.2 | Supporting path planning | 23 |
| 7.1.3 | Providing well-designed paths | 23 |
| 7.1.4 | Making landmarks easy to identify and recognise | 23 |
| 7.1.5 | Providing appropriate navigation techniques | 23 |
| 7.1.6 | Providing navigational aids | 24 |
| 7.1.7 | Understanding the tactile/haptic space | 24 |
| 7.1.8 | Supporting exploratory strategies (procedures) | 24 |
| 7.2 | Reconfiguration | 24 |
| 7.2.1 | Reconfiguring the tactile/haptic space | 24 |
| 7.3 | Interaction techniques | 25 |
| 7.3.1 | Implementing interaction techniques | 25 |
| 7.3.2 | Avoiding unintended oscillation | 25 |
| Annex A (informative) | Overview of the ISO 9241 series | 26 |
| Bibliography | | 30 |