

# ISO 7731:2003-11 (E)

## Ergonomics - Danger signals for public and work areas - Auditory danger signals

---

| <b>Contents</b>              |   | <b>Page</b> |
|------------------------------|---|-------------|
| Foreword .....               |   | iv          |
| Introduction .....           |   | v           |
| <b>1</b>                     | <b>Scope .....</b>  | <b>1</b>    |
| <b>2</b>                     | <b>Normative references .....</b>                                   | <b>1</b>    |
| <b>3</b>                     | <b>Terms, definitions and symbols .....</b>                         | <b>1</b>    |
| <b>4</b>                     | <b>Safety requirements .....</b>                                    | <b>3</b>    |
| 4.1                          | General .....   | 3           |
| 4.2                          | Recognition .....   | 3           |
| 4.2.1                        | Introduction .....  | 3           |
| 4.2.2                        | Audibility .....  | 3           |
| 4.2.3                        | Distinctiveness .....   | 3           |
| 4.2.4                        | Unambiguity .....   | 3           |
| 4.2.5                        | Moving sources .....  | 3           |
| 4.3                          | Review of the signal .....  | 4           |
| 4.4                          | Recommended maximum level of the danger signal .....                | 4           |
| <b>5</b>                     | <b>Test methods .....</b>   | <b>4</b>    |
| 5.1                          | Measurement equipment .....   | 4           |
| 5.2                          | Objective acoustic measurements .....                               | 4           |
| 5.2.1                        | General .....   | 4           |
| 5.2.2                        | Weighted measurements .....   | 4           |
| 5.2.3                        | Measurements made in the frequency domain .....                     | 4           |
| 5.2.4                        | Measurement of the auditory signal with ambient noise present ..... | 5           |
| 5.3                          | Subjective test method .....  | 5           |
| <b>6</b>                     | <b>Design criteria for auditory danger signals .....</b>            | <b>5</b>    |
| 6.1                          | General .....   | 5           |
| 6.2                          | Sound-pressure level .....  | 5           |
| 6.3                          | Spectral characteristics .....                                      | 6           |
| 6.4                          | Temporal characteristics .....                                      | 6           |
| 6.4.1                        | Temporal distribution of the danger signal .....                    | 6           |
| 6.4.2                        | Temporal distribution of the frequencies .....                      | 6           |
| 6.4.3                        | Duration of the danger signals .....                                | 7           |
| 6.5                          | Information required from suppliers .....                           | 7           |
| <b>Annex A (normative)</b>   | <b>Definitions of symbols .....</b>                                 | <b>8</b>    |
| <b>Annex B (normative)</b>   | <b>Calculation of effective masked threshold .....</b>              | <b>9</b>    |
| <b>Annex C (normative)</b>   | <b>Listening test .....</b>   | <b>10</b>   |
| <b>Annex D (informative)</b> | <b>Examples of danger signals .....</b>                             | <b>11</b>   |
| <b>Bibliography .....</b>    |   | <b>17</b>   |