

ISO 1004-1:2013-06 (E)

Information processing - Magnetic ink character recognition - Part 1: Print specifications for E13B

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Character configuration	1
2.1	Designation	1
2.2	Dimensions	2
3	Character spacing and alignment	2
3.1	Spacing	2
3.2	Alignment	2
4	Character skew	2
5	Character tolerances	3
5.1	Dimensions	3
5.2	Average edge definition	3
5.3	Average edge tolerance	3
5.4	Edge irregularity tolerance	3
5.5	Extraneous ink -- attached	12
5.6	Minimum width of horizontal bars	13
6	Voids	13
6.1	Maximum allowable single voids	13
6.2	Maximum allowable combined voids	13
7	Uniformity of ink distribution	13
8	Extraneous ink	15
8.1	Magnetic	15
8.2	Nonmagnetic	15
8.3	Extraneous ink front	17
8.4	Extraneous magnetic ink back	17
9	Debossment	17
10	Embossment	17
11	Signal level	18
11.1	Definition of signal level	18
11.2	Nominal signal level	18
11.3	Relative signal level	18
12	Paper	19
13	Format	19
13.1	Reference edges	19
13.2	Clear band (MICR)	33
13.3	Optical clear band	33

14	Optical clear band background	34
14.1	General	34
14.2	Background reflectance	34
14.3	Print contrast signal (PCS) -- Magnetic ink printed character	34
14.4	Print contrast signal (PCS) -- Within the background	34
15	Permanence of MICR printing	34
15.1	Permanence specification	34
Annex A (informative) Debossment of E-13B font		35
Annex B (informative) MICR Document Sampling References		36
Annex C (informative) Paper Characteristics for MICR		37
Annex D (informative) Unit conversion tables		43
Bibliography		45