ISO 1004-1:2013-06 (E)

Information processing - Magnetic ink character recognition - Part 1: Print specifications for E13B

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Character configuration 1
2.1 Designation 1
2.2 Dimensions 2

3 Character spacing and alignment 2
3.1 Spacing 2
3.2 Alignment 2

4 Character skew 2

5 Character tolerances 3
5.1 Dimensions 3
5.2 Average edge definition 3
5.3 Average edge tolerance 3
5.4 Edge irregularity tolerance 3
5.5 Extraneous ink -- attached 12
5.6 Minimum width of horizontal bars 13

6 Voids 13
6.1 Maximum allowable single voids 13
6.2 Maximum allowable combined voids 13

7 Uniformity of ink distribution 13

8 Extraneous ink 15
8.1 Magnetic 15
8.2 Nonmagnetic 15
8.3 Extraneous ink front 17
8.4 Extraneous magnetic ink back 17

9 Debossment 17

10 Embossment 17

11 Signal level 18
11.1 Definition of signal level 18
11.2 Nominal signal level 18
11.3 Relative signal level 18

12 Paper 19

13 Format 19
13.1 Reference edges 19
13.2 Clear band (MICR) 33
13.3 Optical clear band 33

14 Optical clear band background 34
14.1 General 34
14.2 Background reflectance 34
14.3 Print contrast signal (PCS) -- Magnetic ink printed character 34
14.4 Print contrast signal (PCS) -- Within the background 34

15 Permanence of MICR printing 34
15.1 Permanence specification 34

Annex A (informative) Debossment of E-13B font 35

Annex B (informative) MICR Document Sampling References 36

Annex C (informative) Paper Characteristics for MICR 37

Annex D (informative) Unit conversion tables 43

Bibliography 45