

ISO 3531-2:2022-04 (E)

Financial services - Financial information eXchange session layer - Part 2: FIX session layer

Contents		Page
Foreword		vi
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	FIX session	4
4.1	General	4
4.2	Sequence numbers	5
4.3	Identifying the FIX session	6
4.3.1	General	6
4.3.2	The FIX session profile	6
4.3.3	Identification of FIX session peers	6
4.3.4	Validation of SendingTime(52)	7
4.3.5	Additional fields available for peer identification	7
4.4	Establishing a FIX connection	7
4.4.1	Transport layer requirements	7
4.4.2	Using the TestMessageIndicator(464) to explicitly identify testing	8
4.4.3	Application layer encryption	8
4.4.4	Heartbeat interval	8
4.4.5	Heartbeat interval determination	8
4.4.6	Maximum message size	9
4.4.7	Specifying application version	9
4.4.8	Specifying supported message types	10
4.4.9	Identification of application system and FIX session processor	10
4.4.10	Responding to a request to establish a FIX session	10
4.4.11	Initial synchronization of messages in a FIX connection	13
4.4.12	Synchronization after successful logon	13
4.5	Extended features for FIX session and FIX connection initiation	17
4.5.1	Using NextExpectedMsgSeqNum(789) to synchronize a FIX session	17
4.5.2	Using ResetSeqNumFlag(141) to reset FIX session for 24 h connectivity	19
4.5.3	Using ResetSeqNumFlag(141) to reset FIX session during FIX connection establishment	
19 4.5.4	Using initiator state to restore acceptor session state	19
4.6	Message exchange during a FIX connection	20
4.6.1	FIX connection keep alive (heartbeat)	21
4.6.2	Garbled message processing	21
4.6.3	Missing sequence number	21
4.6.4	Rejecting invalid messages	21
4.6.5	Test Request Processing	22
4.7	FIX connection termination	23
4.7.1	Normal logout processing	24
4.7.2	Logout without acknowledgement from peer	25
4.7.3	Logout with retransmission of missed messages	26
4.7.4	When to terminate a FIX connection by terminating the transport layer connection instead of sending a Logout(35 = 5)	27
4.8	Extended features for FIX connection Termination	27

4.8.1	Using NextExpectedMsgSeqNum(789) when terminating FIX connection due to invalid MsgSeqNum(34)	27
4.9	Message recovery	28
4.9.1	Ordered message processing	28
4.9.2	Request retransmission of messages	28
4.9.3	Responding to a ResendRequest(35 = 2) message	31
ISO 3531-2:2022(E) 4.9.4	Possible duplicates	32
4.9.5	Gap fill process	32
4.9.6	Sequence reset	34
4.9.7	Processing inbound possible duplicate messages (PossDup(43) set to "Y")	35
4.9.8	Processing gaps when receiving FIX session layer messages	35
4.10	Resending an unacknowledged application message	36
4.10.1	The difference between application layer resend and session layer retransmission	37
4.11	FIX session state matrix	38
4.11.1	FIX logon process state transition diagram	40
4.11.2	FIX logout process state transition diagram	41
5	FIX session profiles	42
5.1	FIX.4.2 session profile	42
5.1.1	Profile identification	42
5.1.2	Application version identification	42
5.2	FIX4 session profile	43
5.2.1	Profile identification	43
5.2.2	Application version identification	43
5.3	FIXT session profile	43
5.3.1	Profile identification	43
5.3.2	Multiple application version support over a single FIXT session	43
5.3.3	Session default application version identification	43
5.3.4	Message type default application version	44
5.3.5	Explicit application version per message	44
5.3.6	Use of extension packs	44
5.3.7	Use of a custom application version	45
5.4	Lightweight FIXT (LFIXT session profile)	45
5.4.1	Profile identification	46
5.4.2	Application version identification	46
5.4.3	LFIXT transport layer requirements	46
5.4.4	LFIXT compatible mode	46
5.4.5	LFIXT succinct mode	47
5.4.6	LFIXT and FIXT operating mode interoperability	47
5.4.7	Validation of message sequence numbers	48
5.4.8	Application layer recovery	48
5.4.9	LFIXT initiator connects to LFIXT acceptor	48
5.4.10	FIXT initiator connects to LFIXT acceptor (compatible mode)	50
5.4.11	Receipt of ResendRequest(35 = 2) message from a FIXT peer	53
5.4.12	Processing invalid messages	55
6	FIX message routing	55
6.1	Message routing details - one firm-to-one firm (point-to-point)	55
6.2	Message routing details - third party message routing	55
7	Transmitting alternatively encoded messages over a FIX session	56
7.1	Use of Attachment group	57
8	Components	57
8.1	AttachmentGrp	57
8.2	AttachmentKeywordGrp	58
8.3	HopGrp	58
8.4	MsgTypeGrp	59
8.5	StandardHeader	59
8.6	StandardTrailer	61

9	Messages	61
9.1	Heartbeat message	61
9.2	TestRequest message	62
9.3	ResendRequest message	62
ISO 3531-2:2022(E) 9.4	Reject message	62
9.5	SequenceReset message	63
9.6	Logout message	63
9.7	Logon message	64
9.8	XMLnonFIX message	66
10Fields	66	
11Code sets		72
11.1	ApplLevelRecoveryIndicatorCodeSet	72
11.2	AppIVerIDCodeSet	73
11.3	AttachmentEncodingTypeCodeSet	73
11.4	EncryptMethodCodeSet	74
11.5	GapFillFlagCodeSet	74
11.6	MsgDirectionCodeSet	74
11.7	MsgTypeCodeSet	75
11.8	PossDupFlagCodeSet	75
11.9	PossResendCodeSet	75
11.10	ResetSeqNumFlagCodeSet	76
11.11	SessionRejectReasonCodeSet	76
11.12	SessionStatusCodeSet	77
11.13	TestMessageIndicatorCodeSet	77
Bibliography		78