DIN EN 13906-3:2014-06 (E)

Cylindrical helical springs made from round wire and bar - Calculation and design - Part 3: Torsion springs

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions, symbols, units and abbreviated terms 4
3.1 Terms and definitions 4
3.2 Symbols, units and abbreviated terms 5

4 Theoretical torsion spring diagram 7

5 Design Principles 10
5.1 General 10
5.2 Design of the ends 10
5.3 Mounting of the ends 11
5.4 Design of the spring body 11

6 Types of loading 12
6.1 General 12
6.2 Static and quasi-static loading 12
6.3 Dynamic loading 12

7 Stress correction factor q 13

8 Material property values for the calculations of springs 14

9 Design formulate 15
9.1 Design assumptions 15
9.2 Formulae 15
9.2.1 General 15
9.2.2 Spring torque 15
9.2.3 Angular spring rate 15
9.2.4 Developed length of active coils 16
9.2.5 Nominal diameter of wire or bar 16
9.2.6 Inside coil diameter of the spring 16
9.2.7 Outside coil diameter of the spring 16
9.2.8 Body length of the spring (excluding ends) 16
9.2.9 Number of active coils 16
9.2.10 Torsional angle 16
9.2.11 Spring work 17
9.2.12 Uncorrected bending stress 17
9.2.13 Corrected bending stress 17

10 Permissible bending stress 20
10.1 Permissible bending stress under static or quasi-static loading 20
10.2 Permissible stress range under dynamic loading 20
10.2.1 Fatigue strength values 20
10.2.2 Permissible stress range 20
10.2.3 Lines of equal stress ratio 21

Bibliography 22