

# DIN EN 13906-3:2014-06 (E)

## Cylindrical helical springs made from round wire and bar - Calculation and design - Part 3: Torsion springs

---

| <b>Contents</b>    |   | <b>Page</b> |
|--------------------|---|-------------|
| Foreword .....     |   | 3           |
| 1                  | Scope .....   | 4           |
| 2                  | Normative references .....  | 4           |
| 3                  | Terms and definitions, symbols, units and abbreviated terms .....     | 4           |
| 3.1                | Terms and definitions .....   | 4           |
| 3.2                | Symbols, units and abbreviated terms .....                            | 5           |
| 4                  | Theoretical torsion spring diagram .....                              | 7           |
| 5                  | Design Principles .....   | 10          |
| 5.1                | General .....   | 10          |
| 5.2                | Design of the ends .....  | 10          |
| 5.3                | Mounting of the ends .....  | 11          |
| 5.4                | Design of the spring body .....                                       | 11          |
| 6                  | Types of loading .....  | 12          |
| 6.1                | General .....   | 12          |
| 6.2                | Static and quasi-static loading .....                                 | 12          |
| 6.3                | Dynamic loading .....   | 12          |
| 7                  | Stress correction factor q .....                                      | 13          |
| 8                  | Material property values for the calculations of springs .....        | 14          |
| 9                  | Design formulate .....  | 15          |
| 9.1                | Design assumptions .....  | 15          |
| 9.2                | Formulae .....  | 15          |
| 9.2.1              | General .....   | 15          |
| 9.2.2              | Spring torque .....   | 15          |
| 9.2.3              | Angular spring rate .....   | 15          |
| 9.2.4              | Developed length of active coils .....                                | 16          |
| 9.2.5              | Nominal diameter of wire or bar .....                                 | 16          |
| 9.2.6              | Inside coil diameter of the spring .....                              | 16          |
| 9.2.7              | Outside coil diameter of the spring .....                             | 16          |
| 9.2.8              | Body length of the spring (excluding ends) .....                      | 16          |
| 9.2.9              | Number of active coils .....  | 16          |
| 9.2.10             | Torsional angle .....   | 16          |
| 9.2.11             | Spring work .....   | 17          |
| 9.2.12             | Uncorrected bending stress .....                                      | 17          |
| 9.2.13             | Corrected bending stress .....  | 17          |
| 10                 | Permissible bending stress .....                                      | 20          |
| 10.1               | Permissible bending stress under static or quasi-static loading ..... | 20          |
| 10.2               | Permissible stress range under dynamic loading .....                  | 20          |
| 10.2.1             | Fatigue strength values .....   | 20          |
| 10.2.2             | Permissible stress range .....  | 20          |
| 10.2.3             | Lines of equal stress ratio .....                                     | 21          |
| Bibliography ..... |   | 22          |