

ISO 18137:2015-08 (E)

Leaf springs - Technical specifications

| Contents | | Page |
|------------------------------|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normativereferences | 1 |
| 3 | Termsanddefinitions | 1 |
| 4 | Symbols | 1 |
| 5 | Springtypes | 2 |
| 6 | Technicalrequirements | 7 |
| 6.1 | Materials | 7 |
| 6.2 | Tolerances of spring dimensions and shapes | 7 |
| 6.2.1 | Span | 7 |
| 6.2.2 | Assembled spring width | 7 |
| 6.2.3 | Spring end width | 8 |
| 6.2.4 | Eye inner diameter and bush inner diameter | 8 |
| 6.2.5 | Flank bending | 8 |
| 6.2.6 | Perpendicularity and parallelism of the spring eye | 9 |
| 6.3 | Requirements for characteristic | 10 |
| 6.3.1 | Spring rate | 10 |
| 6.3.2 | Design camber | 10 |
| 6.3.3 | Fatigue | 10 |
| 6.4 | Requirements for manufacturing | 10 |
| 6.4.1 | Hardness | 10 |
| 6.4.2 | Decarburization | 10 |
| 6.4.3 | Shot peening | 10 |
| 6.4.4 | Presetting | 11 |
| 6.4.5 | Lubricant and surface protection | 11 |
| 6.4.6 | Surface conditions | 11 |
| 7 | Designation | 11 |
| Annex A (informative) | Testmethodsofleafsprings | 12 |