

ISO 22705-2:2023-02 (E)

Springs - Measurement and test parameters - Part 2: Cold formed cylindrical helical extension springs

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Symbols and abbreviated terms	2
4	Environmental conditions	3
5	Qualifications of the person(s) performing the work	3
6	Geometries of guiding and supporting devices	3
7	Measuring and testing equipment	3
8	Measurement and test parameter for technical cold formed cylindrical extension springs ..	4
8.1	Free length (L0)	4
8.1.1	General	4
8.1.2	Type of characteristic	4
8.1.3	Measuring and/or testing equipment	4
8.1.4	Conditions of measurement and testing	4
8.1.5	Method of measurement and testing	4
8.1.6	Test location on the product	7
8.2	Body length (LB)	7
8.2.1	General	7
8.2.2	Type of characteristic	7
8.2.3	Measuring and/or testing equipment	8
8.2.4	Conditions of measurement and testing	8
8.2.5	Method of measurement and testing	8
8.2.6	Test location on the product	10
8.3	Spring hook length (LH)	10
8.3.1	General	10
8.3.2	Type of characteristic	10
8.3.3	Measuring and/or testing equipment	11
8.3.4	Conditions of measurement and testing	11
8.3.5	Method of measurement and testing	11
8.3.6	Test location on the product	13
8.4	Hook opening (m)	13
8.4.1	General	13
8.4.2	Type of characteristic	13
8.4.3	Measuring and/or testing equipment	14
8.4.4	Conditions of measurement and testing	14
8.4.5	Method of measurement and testing	14
8.4.6	Test location on the product	15
8.5	Outside diameter (De)	15
8.5.1	General	15
8.5.2	Type of characteristic	15
8.5.3	Measurement and/or testing equipment	16

8.5.4	Conditions of measurement and testing	16
8.5.5	Method of measurement and testing	16
8.5.6	Test location on the product	20
8.6	Inside diameter (Di)	20
8.6.1	General	20
8.6.2	Type of characteristic	20
8.6.3	Measuring and/or testing equipment	20
8.6.4	Conditions of measurement and testing	20
8.6.5	Method of measurement and testing	21
8.6.6	Test location on the product	23
8.7	Total number of coils (nt), number of active coils (n) and coil direction	23
8.7.1	General	23
8.7.2	Type of characteristic	23
8.7.3	Measuring and/or testing equipment	25
8.7.4	Conditions of measurement and testing	25
8.7.5	Method of measurement and testing	25
8.7.6	Test location on the product	26
8.8	Bending radius (r)	26
8.8.1	General	26
8.8.2	Type of characteristic	26
8.8.3	Measuring and/or testing equipment	27
8.8.4	Conditions of measurement and testing	27
8.8.5	Method of measurement and testing	27
8.8.6	Test location on the product	27
8.9	Spring load (F)	28
8.9.1	General	28
8.9.2	Type of characteristic	28
8.9.3	Measuring and/or testing equipment	28
8.9.4	Conditions of measurement and testing	28
8.9.5	Method of measurement and testing	28
8.9.6	Test location on the product	29
8.10	Spring pitch (p) / distance between the coils (u)	29
8.10.1	General	29
8.10.2	Type of characteristic	29
8.10.3	Measuring and/or testing equipment	30
8.10.4	Conditions of measurement and testing	30
8.10.5	Method of measurement and testing	30
8.10.6	Test location on the product	30
8.11	Loop/ Hook position	31
8.11.1	General	31
8.11.2	Type of characteristic	31
8.11.3	Measuring and/or testing equipment	31
8.11.4	Conditions of measurement and testing	32
8.11.5	Method of measurement and testing	32
8.11.6	Test location on the product	32
8.12	Shear-off burr	32
8.12.1	General	32
8.12.2	Type of characteristic	32
8.12.3	Measuring and/or testing equipment	33
8.12.4	Conditions of measurement and testing	33
8.12.5	Method of measurement and testing	33
8.12.6	Test location on the product	34
Annex A (Informative)	Calculation of spring rate R	35
Annex B (Informative)	Calculation of initial tension force (Fi)	36
Annex C (Informative)	Types of hooks	38