ISO 22705-3:2024-04 (E)

Springs - Measurement and test parameters - Part 3: Cold formed cylindrical helical torsion springs

Contents

Page

Foreword ..... **v**

1 Scope **1**

2 Normative references **1**

3 Terms, definitions, symbols and abbreviated terms **1**
3.1 Terms and definitions 1
3.2 Symbols and abbreviated terms 2

4 Environmental conditions **4**

5 Qualifications of the person(s) performing the work **5**

6 Geometries of guiding and supporting devices **5**

7 Measuring and testing equipment **5**

8 Measurement and test parameter for technical cold formed cylindrical torsion springs **5**
8.1 Body length (L_B) 5
8.1.1 General 5
8.1.2 Type of characteristic 5
8.1.3 Measuring and/or testing equipment 5
8.1.4 Conditions of measurement and testing 6
8.1.5 Method of measurement and testing 6
8.1.6 Test location on the product 7
8.2 Outside diameter (D_e) 7
8.2.1 General 7
8.2.2 Type of characteristic 8
8.2.3 Measurement and/or testing equipment 8
8.2.4 Conditions of measurement and testing 8
8.2.5 Method of measurement and testing 8
8.2.6 Test location on the product 10
8.3 Inside diameter (D_i) 10
8.3.1 General 10
8.3.2 Type of characteristic 11
8.3.3 Measurement and/or testing equipment 11
8.3.4 Conditions of measurement and testing 11
8.3.5 Method of measurement and testing 11
8.3.6 Test location on the product 13
8.4 Spring leg length (l) 14
8.4.1 General 14
8.4.2 Type of characteristic 14
8.4.3 Measurement and/or testing equipment 14
8.4.4 Conditions of measurement and testing 15
8.4.5 Method of measurement and testing 15
8.4.6 Test location on the product 15
8.5 Number of coils (n) and coil direction 15
8.5.1 General 15
8.5.2 Type of characteristic 16
8.5.3 Measurement and/or testing equipment 16
8.5.4 Conditions of measurement and testing 16
8.5.5 Method of measurement and testing 16
8.5.6 Test location on the product 17
8.6 Bending radius on legs (r) 17

8.6.1 General 17
8.6.2 Type of characteristic 17
8.6.3 Measurement and/or testing equipment 17
8.6.4 Conditions of measurement and testing 18
8.6.5 Method of measurement and testing 18
8.6.6 Test location on the product 18
8.7 Angle of bend on legs (φ) 18
8.7.1 General 18
8.7.2 Type of characteristic 18
8.7.3 Measurement and/or testing equipment 19
8.7.4 Conditions of measurement and testing 19
8.7.5 Method of measurement and testing 19
8.7.6 Test location on the product 20
8.8 Spring pitch (p)/distance between the coils (u) 20
8.8.1 General 20
8.8.2 Type of characteristic 20
8.8.3 Measurement and/or testing equipment 21
8.8.4 Conditions of measurement and testing 21
8.8.5 Method of measurement and testing 21
8.8.6 Test location on the product 21
8.9 Spring torque (M) 21
8.9.1 General 21
8.9.2 Type of characteristic 21
8.9.3 Measurement equipment 22
8.9.4 Conditions of measurement 22
8.9.5 Method of measurement 22
8.9.6 Test location on the product 23
8.10 Free angle (γ_0) 23
8.10.1 General 23
8.10.2 Type of characteristic 23
8.10.3 Measurement and/or testing equipment 24
8.10.4 Conditions of measurement and testing 24
8.10.5 Method of measurement and testing 24
8.10.6 Test location on the product 24
8.11 Shear-off burr 24
8.11.1 General 24
8.11.2 Type of characteristic 24
8.11.3 Test equipment 25
8.11.4 Conditions of testing 25
8.11.5 Method of testing 25
8.11.6 Test location on the product 25
Annex A (informative) **Calculation of spring rate R_M** **26**
Annex B (informative) **Type of legs** **27**
Annex C (informative) **Measurement of the length of leg *l*** **28**
Annex D (informative) **Offset of leg *c*** **29**
Bibliography **30**