DIN EN ISO 22705-3:2026-08 (E)

Springs - Measurement and test parameters - Part 3: Cold formed cylindrical helical torsion springs (ISO 22705-3:2024)

Contents

Page

8.6.6 Test location on the product 18
8.7 Angle of bend on legs () 18
8.7.1 General 18
8.7.2 Type of characteristic 18
8.7.3 Measurement and/or testing equipment 19
8.7.4 Conditions of measurement and testing 19
8.7.5 Method of measurement and testing 19
8.7.6 Test location on the product 20
8.8 Spring pitch (p)/distance between the coils (u) 20
8.8.1 General 20
8.8.2 Type of characteristic 20
8.8.3 Measurement and/or testing equipment 21
8.8.4 Conditions of measurement and testing 21
8.8.5 Method of measurement and testing 21
8.8.6 Test location on the product 21
8.9 Spring torque (M) 21
8.9.1 General 21
8.9.2 Type of characteristic 21
8.9.3 Measurement equipment 22
8.9.4 Conditions of measurement 22
8.9.5 Method of measurement 22
8.9.6 Test location on the product 23
8.10 Free angle (0) .....
8.10.1 General 23
8.10.2 Type of characteristic 23
8.10.3 Measurement and/or testing equipment 24
8.10.4 Conditions of measurement and testing 24
8.10.5 Method of measurement and testing 24
8.10.6 Test location on the product 24
8.11 Shear-off burr 24
8.11.1 General 24
8.11.2 Type of characteristic 24
8.11.3 Test equipment 25
8.11.4 Conditions of testing 25
8.11.5 Method of testing 25
8.11.6 Test location on the product 25

Annex A (informative) Calculation of spring rate RM 26

Annex B (informative) Type of legs 27

Annex C (informative) Measurement of the length of leg l 28

Annex D (informative) Offset of leg c 29

Bibliography 30