DIN EN ISO 22705-1:2026-08 (E)

Springs - Measurement and test parameters - Part 1: Cold formed cylindrical helical compression springs (ISO 22705-1:2021)

Contents

Page

Foreword ..... **v**

1 Scope **1**

2 Normative references **1**

3 Terms, definitions, symbols and abbreviated terms **1**
3.1 Terms and definitions 1
3.2 Symbols and abbreviated terms 2

4 Environmental conditions **3**

5 Qualifications of the person(s) performing the work **3**

6 Geometries of guiding and supporting devices **4**

7 Measuring and testing equipment **4**

8 Measurement and test parameter for technical cold formed cylindrical compression springs **4**
8.1 Free length (L_0) 4
8.1.1 General 4
8.1.2 Type of characteristic 4
8.1.3 Measuring and/or testing equipment 4
8.1.4 Conditions of measurement and testing 5
8.1.5 Method of measurement and testing 5
8.1.6 Test location on the product 6
8.2 Outside diameter (D_e) 6
8.2.1 General 6
8.2.2 Type of characteristic 6
8.2.3 Measurement and/or testing equipment 7
8.2.4 Conditions of measurement and testing 7
8.2.5 Method of measurement and testing 7
8.2.6 Test location on the product 9
8.3 Inside diameter (D_i) 10
8.3.1 General 10
8.3.2 Type of characteristic 10
8.3.3 Measuring and/or testing equipment 10
8.3.4 Conditions of measurement and testing 10
8.3.5 Method of measurement and testing 10
8.3.6 Test location on the product 12
8.4 Total number of coils (n_t), number of active coils (n) and coil direction 13
8.4.1 General 13
8.4.2 Type of characteristic 13
8.4.3 Measuring and/or testing equipment 15
8.4.4 Conditions of measurement and testing 15
8.4.5 Method of measurement and testing 15
8.4.6 Test location on the product 16
8.5 Applied end coils 16
8.5.1 General 16
8.5.2 Type of characteristic 16
8.5.3 Measuring and/or testing equipment 17
8.5.4 Conditions of measurement and testing 17
8.5.5 Method of measurement and testing 17
8.5.6 Test location on the product 17

8.6 Solid length (L_c)/solid force (F_c) 17
8.6.1 General 17
8.6.2 Type of characteristics 17
8.6.3 Measuring and/or testing equipment 18
8.6.4 Conditions of measurement and testing 18
8.6.5 Method of measurement and testing 18
8.6.6 Test location on the product 19
8.7 Spring load (F) 19
8.7.1 General 19
8.7.2 Type of characteristic 19
8.7.3 Measuring and/or testing equipment 19
8.7.4 Conditions of measurement and testing 19
8.7.5 Method of measurement and testing 20
8.7.6 Test location on the product 20
8.8 Spring pitch (p)/distance between the coils 20
8.8.1 General 20
8.8.2 Type of characteristic 20
8.8.3 Measuring and/or testing equipment 21
8.8.4 Conditions of measurement and testing 21
8.8.5 Method of measurement and testing 21
8.8.6 Test location on the product 21
8.9 Ground surface/angle 21
8.9.1 General 21
8.9.2 Type of characteristic 22
8.9.3 Measuring and/or testing equipment 22
8.9.4 Conditions of measurement and testing 23
8.9.5 Method of measurement and testing 23
8.9.6 Test location on the product 23
8.10 Perpendicularity (e_1) 23
8.10.1 General 23
8.10.2 Type of characteristic 23
8.10.3 Measuring and/or testing equipment 24
8.10.4 Conditions of measurement and testing 24
8.10.5 Method of measurement and testing 24
8.10.6 Test location on the product 25
8.11 Parallelism (e_2) 25
8.11.1 General 25
8.11.2 Type of characteristic 25
8.11.3 Measuring and/or testing equipment 25
8.11.4 Conditions of measurement and testing 26
8.11.5 Method of measurement and testing 26
8.11.6 Test location on the product 26
8.12 Shear-off burr 26
8.12.1 General 26
8.12.2 Type of characteristic 27
8.12.3 Measuring and/or testing equipment 27
8.12.4 Conditions of measurement and testing 27
8.12.5 Method of measurement and testing 27
8.12.6 Test location on the product 28
Annex A (informative) **Calculation of spring rate (R)** **29**
Bibliography **30**