

DIN EN ISO 22705-1:2026-08 (E)

Springs - Measurement and test parameters - Part 1: Cold formed cylindrical helical compression springs (ISO 22705-1:2021)

Contents	Page
Foreword	v
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	1
3.1 Terms and definitions	1
3.2 Symbols and abbreviated terms	2
4 Environmental conditions	3
5 Qualifications of the person(s) performing the work	3
6 Geometries of guiding and supporting devices	4
7 Measuring and testing equipment	4
8 Measurement and test parameter for technical cold formed cylindrical compression springs	4
8.1 Free length (L_0)	4
8.1.1 General	4
8.1.2 Type of characteristic	4
8.1.3 Measuring and/or testing equipment	4
8.1.4 Conditions of measurement and testing	5
8.1.5 Method of measurement and testing	5
8.1.6 Test location on the product	6
8.2 Outside diameter (D_e)	6
8.2.1 General	6
8.2.2 Type of characteristic	6
8.2.3 Measurement and/or testing equipment	7
8.2.4 Conditions of measurement and testing	7
8.2.5 Method of measurement and testing	7
8.2.6 Test location on the product	9
8.3 Inside diameter (D_i)	10
8.3.1 General	10
8.3.2 Type of characteristic	10
8.3.3 Measuring and/or testing equipment	10
8.3.4 Conditions of measurement and testing	10
8.3.5 Method of measurement and testing	10
8.3.6 Test location on the product	12
8.4 Total number of coils (n_t), number of active coils (n) and coil direction	13
8.4.1 General	13
8.4.2 Type of characteristic	13
8.4.3 Measuring and/or testing equipment	15
8.4.4 Conditions of measurement and testing	15
8.4.5 Method of measurement and testing	15
8.4.6 Test location on the product	16
8.5 Applied end coils	16
8.5.1 General	16
8.5.2 Type of characteristic	16
8.5.3 Measuring and/or testing equipment	17
8.5.4 Conditions of measurement and testing	17
8.5.5 Method of measurement and testing	17
8.5.6 Test location on the product	17

8.6	Solid length (L_c)/solid force (F_c).....	17
8.6.1	General.....	17
8.6.2	Type of characteristics.....	17
8.6.3	Measuring and/or testing equipment.....	18
8.6.4	Conditions of measurement and testing.....	18
8.6.5	Method of measurement and testing.....	18
8.6.6	Test location on the product.....	19
8.7	Spring load (F).....	19
8.7.1	General.....	19
8.7.2	Type of characteristic.....	19
8.7.3	Measuring and/or testing equipment.....	19
8.7.4	Conditions of measurement and testing.....	19
8.7.5	Method of measurement and testing.....	20
8.7.6	Test location on the product.....	20
8.8	Spring pitch (p)/distance between the coils.....	20
8.8.1	General.....	20
8.8.2	Type of characteristic.....	20
8.8.3	Measuring and/or testing equipment.....	21
8.8.4	Conditions of measurement and testing.....	21
8.8.5	Method of measurement and testing.....	21
8.8.6	Test location on the product.....	21
8.9	Ground surface/angle.....	21
8.9.1	General.....	21
8.9.2	Type of characteristic.....	22
8.9.3	Measuring and/or testing equipment.....	22
8.9.4	Conditions of measurement and testing.....	23
8.9.5	Method of measurement and testing.....	23
8.9.6	Test location on the product.....	23
8.10	Perpendicularity (e_1).....	23
8.10.1	General.....	23
8.10.2	Type of characteristic.....	23
8.10.3	Measuring and/or testing equipment.....	24
8.10.4	Conditions of measurement and testing.....	24
8.10.5	Method of measurement and testing.....	24
8.10.6	Test location on the product.....	25
8.11	Parallelism (e_2).....	25
8.11.1	General.....	25
8.11.2	Type of characteristic.....	25
8.11.3	Measuring and/or testing equipment.....	25
8.11.4	Conditions of measurement and testing.....	26
8.11.5	Method of measurement and testing.....	26
8.11.6	Test location on the product.....	26
8.12	Shear-off burr.....	26
8.12.1	General.....	26
8.12.2	Type of characteristic.....	27
8.12.3	Measuring and/or testing equipment.....	27
8.12.4	Conditions of measurement and testing.....	27
8.12.5	Method of measurement and testing.....	27
8.12.6	Test location on the product.....	28
	Annex A (informative) Calculation of spring rate (R).....	29
	Bibliography.....	30