

ISO/TR 18476:2017-06 (E)

Ophthalmic optics and instruments - Free form technology - Spectacle lenses and measurement

| Contents | | Page |
|------------------------------|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Technical introduction | 1 |
| 4.1 | Preliminaries | 1 |
| 4.2 | What is free form? | 1 |
| 4.3 | Does free form equal better vision? | 2 |
| 4.4 | Classification | 2 |
| 5 | Manufacturing | 3 |
| 5.1 | General | 3 |
| 5.2 | Conventional surfacing | 4 |
| 5.3 | Free form surfacing | 5 |
| 5.4 | Comparison of conventional and free form manufacturing | 6 |
| 6 | Potential benefits of free form lens calculation | 7 |
| 6.1 | Oblique astigmatism | 7 |
| 6.2 | Limitations of conventional lenses | 9 |
| 6.3 | Potential benefit of free form lens design | 10 |
| 6.4 | Optimization for prescription | 11 |
| 6.5 | Customization for the as-worn position | 12 |
| 6.5.1 | Explaining the as-worn position | 12 |
| 6.5.2 | As-worn position and verification power | 13 |
| 6.6 | Customization for the frame size | 14 |
| 6.7 | Personalization of the lens design | 15 |
| 7 | Measurement and quality control | 16 |
| 7.1 | Lens performance | 16 |
| 7.2 | Conformity with standards | 16 |
| 7.3 | Design integrity and process control | 17 |
| 7.3.1 | General | 17 |
| 7.3.2 | Surface shape measurement | 17 |
| 7.3.3 | Through power measurement | 17 |
| 7.4 | Measuring the as-worn position | 18 |
| 7.5 | Inspection gates of the manufacturing process | 21 |
| Annex A (informative) | Typical dispensing flowchart | 22 |
| Annex B (informative) | Measurement technology | 23 |
| Annex C (informative) | Glossary of terms and their descriptions | 28 |
| Bibliography | | 30 |