

# ISO 5834-4:2019 (E)

## Implants for surgery — Ultra-high-molecular-weight polyethylene — Part 4: Oxidation index measurement method

---

### Contents

|     |  |
|-----|--|
|     | Foreword   |
|     | Introduction                                       |
| 1   | Scope  |
| 2   | Normative references                               |
| 3   | Terms and definitions                              |
| 4   | Test articles                                      |
| 5   | Materials and apparatus                            |
| 5.1 | Materials  |
| 5.2 | Apparatus  |
| 6   | Significance and use                               |
| 7   | Procedure  |
| 7.1 | Preparation of test specimens                      |
| 7.2 | Configuration of test specimen in the spectrometer |
| 7.3 | Preparation of the infrared spectrometer           |
| 8   | Calculations                                       |
| 8.1 | General  |
| 8.2 | Oxidation peak area                                |
| 8.3 | Normalization peak area                            |
| 8.4 | Oxidation index                                    |
| 8.5 | Depth locator                                      |
| 8.6 | Sample's surface oxidation index                   |
| 8.7 | Sample's bulk oxidation index                      |
| 8.8 | Sample's oxidation index profile                   |
| 9   | Reports  |
| 9.1 | General  |
| 9.2 | Information concerning the material                |
| 9.3 | Sample information                                 |
| 9.4 | IR spectrometer parameters                         |
| 9.5 | Calculation methods                                |
| 9.6 | Sample's calculated surface oxidation index        |
| 9.7 | Sample's calculated bulk oxidation index           |
| 9.8 | Sample's calculated oxidation index profile        |

Page count: 8