

ISO 18526-2:2020-02 (E)

Eye and face protection - Test methods - Part 2: Physical optical properties

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | vii |
| Introduction | | viii |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Preparatory information | 1 |
| 5 | General test requirements | 2 |
| 6 | Test methods for measuring transmittance -- General | 2 |
| 6.1 | Uncertainty of measurement | 2 |
| 6.2 | Reporting compliance | 3 |
| 6.3 | Applicability | 3 |
| 6.4 | Position and direction of measurement | 3 |
| 6.5 | Wavelength intervals | 3 |
| 6.6 | Test report | 3 |
| 7 | Luminous transmittance | 3 |
| 7.1 | Calculations of luminous transmittance from spectral values | 3 |
| 7.2 | Test report | 3 |
| 7.3 | Broadband method of measurement of luminous transmittance | 4 |
| 7.3.1 | Apparatus | 4 |
| 7.3.2 | Calibration | 4 |
| 7.3.3 | Procedure | 4 |
| 7.3.4 | Test reports for luminous transmittance values | 4 |
| 7.4 | Measurement of uniformity of luminous transmittance | 4 |
| 7.4.1 | Unmounted filter covering one eye | 4 |
| 7.4.2 | Filter covering both eyes | 6 |
| 7.5 | Transmittance matching at right and left reference points | 9 |
| 7.5.1 | Test method | 9 |
| 7.5.2 | Calculations | 10 |
| 7.5.3 | Test report | 10 |
| 8 | Ultraviolet transmittance | 10 |
| 8.1 | General | 10 |
| 8.2 | Spectral transmittance and mean spectral transmittance | 10 |
| 8.3 | Solar UV transmittance | 10 |
| 8.4 | Solar UV-A transmittance | 10 |
| 8.5 | Solar UV-B transmittance | 10 |
| 8.6 | Mean UV-A transmittance | 10 |
| 8.7 | Mean UV-B transmittance | 11 |
| 8.8 | Mean 380 nm to 400 nm transmittance | 11 |
| 8.9 | Test report | 11 |
| 9 | Blue-light transmittance | 11 |
| 9.1 | Solar blue-light transmittance | 11 |
| 9.1.1 | Calculation of solar blue-light transmittance from spectral values | 11 |

| | | |
|--------|---|----|
| 9.1.2 | Broadband method of measurement of solar blue-light transmittance | 11 |
| 9.2 | Blue-light transmittance from artificial sources | 11 |
| 9.2.1 | Calculation of blue-light transmittance from artificial sources from spectral values | 11 |
| 9.2.2 | Broadband method of measurement of blue-light transmittance from artificial sources ... | 12 |
| 9.2.3 | Test report | 12 |
| 10 | IR transmittance | 12 |
| 10.1 | Near IR transmittance | 12 |
| 10.1.1 | Calculation | 12 |
| 10.2 | IR-A transmittance | 12 |
| 10.2.1 | Calculation | 12 |
| 10.3 | IR-B transmittance | 12 |
| 10.3.1 | Calculation | 12 |
| 10.4 | Solar IR transmittance | 12 |
| 10.4.1 | Calculation | 12 |
| 10.5 | Test report | 12 |
| 11 | Relative visual attenuation coefficient for traffic signal light detection, Q_{signal} | 13 |
| 11.1 | Calculation | 13 |
| 11.2 | Test report | 13 |
| 12 | Spectral reflectance | 13 |
| 12.1 | Uncertainty of measurement | 13 |
| 12.2 | Position and direction of measurement | 13 |
| 12.2.1 | Specular spectral reflectance | 13 |
| 12.2.2 | Total spectral reflectance (specular included) | 13 |
| 12.2.3 | Total spectral reflectance (specular excluded) | 14 |
| 12.2.4 | 0°/45° and 45°/0° geometry | 14 |
| 12.3 | Wavelength intervals | 14 |
| 12.4 | Test report | 14 |
| 13 | Luminous reflectance | 14 |
| 13.1 | Calculations | 14 |
| 13.2 | Test report | 14 |
| 13.3 | Luminous reflectance of mesh | 14 |
| 14 | Scattered light | 15 |
| 14.1 | Wide angle scatter | 15 |
| 14.1.1 | Principle | 15 |
| 14.1.2 | Apparatus | 15 |
| 14.1.3 | Test sample | 16 |
| 14.1.4 | Test procedure | 16 |
| 14.1.5 | Calculation | 16 |
| 14.1.6 | Test report | 17 |
| 14.2 | Narrow angle scatter | 17 |
| 14.2.1 | Principle | 17 |
| 14.2.2 | Test methods | 18 |
| 14.2.3 | Test report | 23 |
| 15 | Polarization | 23 |
| 15.1 | Plane of transmission | 23 |
| 15.1.1 | Apparatus | 23 |
| 15.1.2 | Test procedure | 23 |
| 15.1.3 | Test report | 24 |
| 15.2 | Polarizing efficiency | 24 |
| 15.2.1 | Principle | 24 |
| 15.2.2 | Test procedure for the spectrophotometric method | 25 |
| 15.2.3 | Test report | 25 |
| 15.2.4 | Test procedure for the broadband method | 25 |
| 15.2.5 | Test report | 26 |

| | | |
|---------|--|----|
| 16 | Photochromic lenses | 26 |
| 16.1 | Light source(s) to approximate the spectral distribution of solar radiation for air mass 2 for testing | 26 |
| 16.1.1 | Radiation source using one lamp | 26 |
| 16.1.2 | Radiation source using two lamps | 27 |
| 16.2 | Conditioning for luminous transmittance in the faded state | 27 |
| 16.3 | Measurement | 28 |
| 16.3.1 | Principle | 28 |
| 16.3.2 | Faded state | 28 |
| 16.3.3 | Darkened states | 28 |
| 17 | Automaticweldingfilters | 29 |
| 17.1 | General | 29 |
| 17.2 | Luminous transmittance in the light state | 29 |
| 17.2.1 | Measurement | 29 |
| 17.2.2 | Test report | 30 |
| 17.3 | Luminous transmittance in the dark state | 30 |
| 17.3.1 | Measurement | 30 |
| 17.3.2 | Test report | 30 |
| 17.4 | Shade number of welding filters with automatic shade number setting | 30 |
| 17.4.1 | Principle | 30 |
| 17.4.2 | Apparatus | 31 |
| 17.4.3 | Test procedure | 31 |
| 17.4.4 | Test report | 31 |
| 17.5 | Luminous transmittance variation over time | 31 |
| 17.5.1 | Principle | 31 |
| 17.5.2 | Apparatus | 32 |
| 17.5.3 | Test procedure | 32 |
| 17.5.4 | Test report | 32 |
| 17.6 | Blue-light transmittance for artificial sources | 32 |
| 17.6.1 | Measurement | 32 |
| 17.6.2 | Test report | 32 |
| 17.7 | Uniformity of luminous transmittance for flat filters | 32 |
| 17.7.1 | Filter covering both eyes | 32 |
| 17.8 | Angular dependence of luminous transmittance for flat filters | 33 |
| 17.8.1 | Principle | 33 |
| 17.8.2 | Apparatus | 33 |
| 17.8.3 | Test procedure | 34 |
| 17.8.4 | Test report | 37 |
| 17.9 | Angular dependence and uniformity of luminous transmittance for curved filters | 37 |
| 17.9.1 | Principle | 37 |
| 17.9.2 | Apparatus | 37 |
| 17.9.3 | Procedure | 38 |
| 17.9.4 | Test report | 39 |
| 17.10 | Transmittance matching at right and left reference points | 39 |
| 17.10.1 | Procedure | 39 |
| 17.10.2 | Test report | 39 |
| 17.11 | Switching time | 39 |
| 17.11.1 | Principle | 39 |
| 17.11.2 | Apparatus | 39 |
| 17.11.3 | Procedure | 39 |
| 17.11.4 | Uncertainty of measurement | 40 |
| 17.11.5 | Test report | 40 |
| 17.12 | Holding time | 40 |
| 17.12.1 | Principle | 40 |
| 17.12.2 | Apparatus | 40 |
| 17.12.3 | Procedure | 40 |
| 17.12.4 | Uncertainty of measurement | 40 |
| 17.12.5 | Test report | 40 |
| 17.13 | Manual control of dark state | 40 |
| 17.13.1 | Procedure | 40 |
| 17.13.2 | Test report | 41 |

| | | |
|--|--|----|
| 17.14 | Optical sensitivity of welding detection | 41 |
| 17.14.1 | Principle | 41 |
| 17.14.2 | Apparatus | 41 |
| 17.14.3 | Measuring equipment | 42 |
| 17.14.4 | Trigger light source (L) | 43 |
| 17.14.5 | Calibration procedure for the trigger light source (L) | 44 |
| 17.14.6 | Higher intensity light source (I) | 44 |
| 17.14.7 | Lower intensity light source (F) | 45 |
| 17.14.8 | Test procedure | 46 |
| 17.14.9 | Test report | 46 |
| Annex A (normative) Application of uncertainty of measurement | | 47 |
| Annex B (informative) Sources of uncertainty in spectrophotometry and their estimation and control | | 50 |
| Annex C (informative) Definitions in summation form | | 58 |
| Annex D (normative) Spectral functions for the calculation of transmittance and reflectance values | | 63 |
| Annex E (informative) Generic description of automatic welding filters and guidance on illumination during testing | | 73 |
| Bibliography | | 77 |