

ISO 14490-5:2021 (E)

Optics and photonics — Test methods for telescopic systems — Part 5: Test methods for transmittance

Contents

| | |
|---------|--|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Principle |
| 5 | Test arrangement |
| 5.1 | General |
| 5.2 | Radiation source and condenser |
| 5.3 | Monochromator or set of filters |
| 5.4 | Collimator |
| 5.5 | Aperture stop |
| 5.6 | Specimen mounting |
| 5.7 | Integrating sphere |
| 5.8 | Radiation detector |
| 5.9 | Selectable diaphragm as field stop |
| 6 | Procedure |
| 6.1 | Preparation of the test arrangement |
| 6.2 | Determination of the measurement values |
| 6.3 | Further test methods |
| 7 | Precision of the measurement |
| 8 | Presentation of the results |
| 9 | Analysis |
| 9.1 | Effective transmittance for photopic vision |
| 9.2 | Effective transmittance for scotopic vision |
| 10 | Test report |
| Annex A | (informative) Calibration procedure for the radiation detector/measuring instrument |
| A.1 | Control of proportionality of the photocurrent measured by the instrument to the illuminance on the light-sensitive surface of the radiation detector |
| A.2 | Checking the independence of readings of the indicating device in relation to the size of the illuminated surface of the radiation detector in the case of constant light flux |
| Annex B | (informative) Trichromatic coefficients and colour contribution index |
| B.1 | Trichromatic coefficients |
| B.2 | Values for the colour contribution index |
| B.3 | CIELAB values |
| B.4 | CIELUV values |