ISO 16436-1:2026-08 (E)

Implants for surgery - Wear of total shoulder-joint prostheses - Part 1: Methodology for simulator wear testing of anatomic total shoulder-joint prostheses

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Principle 6
4.1 Reference position 6
4.2 Physiological motion simulated 8
4.3 Component alignment in the knee simulator 8

5 Test specimens, soak control specimen, sample size and lubricant 9
5.1 Test specimens 9
5.1.1 General 9
5.1.2 Assembly of components and interlocks 9
5.1.3 Permitted component adaptations 10
5.2 Soak control specimen 10
5.3 Sample size 10
5.4 Lubricant (fluid test medium) 10

6 Apparatus 11

7 Procedure 14

8 Test report 16

9 Disposal of test specimens 17

Annex A (normative) Details of axial force target waveform for the test cycle described in Figure 7 a) 18

Annex B (normative) Details of shear force target waveform for the test cycle described in Figure 7 b) 21

Annex C (normative) Details of rotation around x target waveform for the test cycle described in Figure 7 c) 24

Annex D (normative) Details of rotation around z target waveform for the test cycle described in Figure 7 d) 27

Annex E (informative) Principles of the definition of the tolerance envelopes around each target waveform 30

Bibliography 31