ISO 5833:2026-10 (E)

Implants for surgery - Acrylic resin cements

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Liquid component 1
4.1 Appearance 1
4.2 Stability 2
4.3 Accuracy of contents 2

5 Powder component 2
5.1 General 2
5.2 Appearance 2
5.3 Accuracy of contents 2
5.4 Initiator agent concentration 2

6 Liquid-powder mixture intended for syringe usage 2
6.1 Setting properties, test methods and requirements 2
6.2 Extrusion 3

7 Liquid-powder mixture intended for use in dough state 3
7.1 Setting properties, test methods and requirements 3
7.2 Intrusion 3

8 Liquid-powder mixture intended for dual usage (both syringe and dough state usage) 3
8.1 Setting properties, test methods and requirements 3
8.2 Intrusion and extrusion 3

9 Set and polymerized cement 4
9.1 General 4
9.2 Monitoring leachable monomer from set and polymerized cement 4

10 Packaging 4

11 Labelling 4
11.1 Unit package 4
11.2 Accompanying documentation 5

12 Biocompatibility 5
12.1 General 5

Annex A (normative) Determination of stability of liquid component 6

Annex B (normative) Determination of doughing time of liquid-powder mixture of cement intended for dough usage 8

Annex C (normative) Determination of maximum temperature and setting time of liquid- powder mixture 10

Annex D (normative) Determination of intrusion of liquid-powder mixture of cement intended for dough usage 14

Annex E (normative) Determination of compressive strength of polymerized cement 17

Annex F (normative) Determination of bending modulus and bending strength of polymerized cement 21

Bibliography 25