

DIN EN ISO 22675:2007-04 (E)

Prosthetics - Testing of ankle-foot devices and foot units - Requirements and test methods (ISO 22675:2006)

Contents		Page
Foreword		6
Introduction		7
1	Scope	8
2	Normative references	9
3	Terms and definitions	9
4	Designations and symbols of test forces	9
5	Strength and related performance requirements and conditions of use	10
6	Coordinate system and test configurations	11
6.1	General	11
6.2	Origin and axes of the coordinate system	11
6.3	Reference points	12
6.4	Test force F	13
6.5	Line of application of test force F	13
6.6	Lines of action of resultant reference forces FR1 and FR2	13
6.7	Longitudinal axis of the foot and effective ankle joint centre	13
6.7.1	General	13
6.7.2	Longitudinal axis of the foot	13
6.7.3	Effective ankle-joint centre, CA	14
7	Test loading conditions and test loading levels	15
7.1	Test loading conditions	15
7.2	Test loading levels	15
8	Values of test forces, dimensions and cycles	16
9	Compliance	23
9.1	General	23
9.2	Particular arrangements and requirements concerning the part required to connect an ankle-foot device or foot unit to the remainder of a prosthetic structure	24
9.2.1	Arrangements for testing	24
9.2.2	Requirements for claiming compliance	24
9.3	Number of tests and test samples required to claim compliance with this International Standard	24
9.4	Multiple use of test samples	25
9.4.1	General	25
9.4.2	Restriction	25
9.5	Testing at particular test loading levels not specified in this International Standard	25
10	Test samples	26
10.1	Selection of test samples	26
10.1.1	General	26
10.1.2	Selection of ankle-foot devices and foot units of appropriate size of foot	26
10.2	Types of test sample	27
10.2.1	Complete structure	27

10.2.2	Partial structure	27
10.3	Preparation of test samples	27
10.4	Identification of test samples	28
10.5	Alignment of test samples	28
10.6	Worst-case alignment position of test samples	28
11	Responsibility for test preparation	30
12	Test submission document	31
12.1	General requirements	31
12.2	Information required for test samples	31
12.3	Information required for tests	32
12.3.1	General	32
12.3.2	For all tests	32
12.3.3	For the static proof test and the static ultimate strength test	32
12.3.4	For the static ultimate strength test	32
12.3.5	For the cyclic test	32
13	Equipment	33
13.1	General	33
13.2	End attachments	33
13.2.1	General	33
13.2.2	Proof test of end attachments	33
13.3	Jig (optional)	35
13.4	Test equipment	35
13.4.1	Test equipment to perform static heel and forefoot loading	35
13.4.2	Test equipment to perform cyclic loading	37
14	Accuracy	44
14.1	General	44
14.2	Accuracy of equipment	44
14.3	Accuracy of procedure	45
15	Test principles	45
15.1	General	45
15.2	Static test procedure	46
15.3	Cyclic test procedure	46
16	Test procedures	46
16.1	Test loading requirements	46
16.1.1	Preparation for test loading	46
16.1.2	Test loading conditions	50
16.2	Static proof test	50
16.2.1	Test method	50
16.2.2	Performance requirement	52
16.2.3	Compliance conditions	52
16.3	Static ultimate strength test	54
16.3.1	Test method	54
16.3.2	Performance requirements	57
16.3.3	Compliance conditions	57
16.4	Cyclic test	59
16.4.1	Test method	59
16.4.2	Performance requirements	61
16.4.3	Compliance conditions	62
17	Test laboratory/facility log	65
17.1	General requirements	65
17.2	Specific requirements	65
18	Test report	65
18.1	General requirements	65
18.2	Specific requirements	66

18.3	Options	66
19	Classification and designation	66
19.1	General	66
19.2	Examples of classification and designation	66
20	Labelling	67
20.1	General	67
20.2	Use of mark "*" and warning symbol	68
20.3	Examples of label layout	68
20.4	Label placement	69
Annex A (informative) Reference data for the specification of the test loading conditions and test loading levels of this International Standard		70
Annex B (informative) Guidance on the application of an alternative static ultimate strength test		78
Annex C (informative) Guidance on the application of an additional test loading level P6		79
Annex D (informative) Summary of the records to be entered in the test laboratory/facility log		81
Annex E (informative) Information on Technical Report ISO/TR 22676 [1]		87
Annex F (informative) Reference to the essential principles of safety and performance of medical devices according to ISO/TR 16142		98
Bibliography		99
Annex ZA (informative) Clauses of this European Standard addressing essential requirements		
Figure 1 -- Coordinate system with reference parameters		12
Figure 2 -- Determination of longitudinal axis of foot (see 6.7.2) and effective ankle-joint centre CA (see 6.7.3)		14
Figure 3 -- Illustration of reference points for the establishment of thresholds listed in Table 10 for specification of the loading profile of the cyclic test		21
Figure 4 -- Illustration of specific set-up of left-sided test sample with top load application point PT 30		
Figure 5 -- Diagrammatic view of test equipment according to 13.4.1 and 13.4.2 with test sample		42
Figure 6 -- Profiles of test force $F_c(t)$ and tilting angle (t) as synchronized functions of time, determining the loading condition of the cyclic test of this International Standard		43
Figure 7 -- Test force $F_c(t)$ of test loading level P5 as function of tilting angle (t) of foot platform		44
Figure 8 -- Preparation for test loading of static test procedure [see 16.1.1 a)]		49
Figure 9 -- Flowchart for the static proof test specified in 16.2.1		53
Figure 10 -- Flowchart for the static ultimate strength test specified in 16.3.1		58
Figure 11 -- Flowchart for the cyclic test specified in 16.4.1 Continued on Figure 12		63
Figure 12 -- Flowchart for the cyclic test specified in 16.4.1 Continued from Figure 11		64
Figure 13 -- General concept for the label layout		67
Figure 14 -- Models for the label layout		68
Figure A.1 -- Illustration of different components of loading		76

Figure A.2 -- Illustration of the dependence of the position of the top load application point PT on the foot length L -- (see A.2.2.3)	77
Figure E.1 -- Effect of f-position of tilting axis TA of foot platform on the elevation E of the foot at the instants of heel contact and toe-off	90
Figure E.2 -- Effect of u-position of tilting axis TA of foot platform on the A/P displacement f of the foot at the instant of toe-off	91
Figure E.3 -- Illustration of the effect of A-P displacement f on the angular movement of the test sample about the top load application point PT	92
Figure E.4 -- Illustration of possibilities of transposing the top load application point PT for compensation of the dependence of the position of the tilting axis TA of the foot platform on the foot length L	95
Figure E.5 -- Illustration of the effect of a fixed compromise offset $u_{TA, C}$ of the tilting axis TA of the foot platform on the A-P displacement f at the foot [see E.3.4.2 c) 2)]	96
Table 1 -- Designations and symbols of test forces	9
Table 2 -- Categories of strength addressed in this International Standard, together with the related performance requirements and test methods for their verification	10
Table 3 -- Test forces and relevant references	16
Table 4 -- Values of bottom offsets $f_{B1, L}$ (heel) and $f_{B2, L}$ (forefoot) for given values of foot length L, relevant to the design and/or adjustment of the rigid foot dummy required to simulate or other provisions of EU Directives	100
the effective lever arms of an ankle-foot device or foot unit in the proof test of end attachments (see 13.2.2)	17
Table 5 -- Test forces of the proof test of end attachments for test loading levels P5, P4 and P3 (see 13.2.1)	17
Table 6 -- Total length of test samples and segmental lengths of end attachments	18
Table 7 -- Coordinates of top load application point PT and tilting axis TA of foot platform based on given values of foot length L, for all test loading levels	19
Table 8 -- Angles of toe-out position of foot and specific tilting positions of foot platform, for all test loading levels	19
Table 9 -- Test forces for all tests and prescribed number of cycles for the cyclic test, for test loading levels P5, P4 and P3 (see 16.2, 16.3 and 16.4)	20
Table 10 -- Thresholds according to Figure 3 for specification of the application of the loading profile of the cyclic test	22
Table 11 -- Data specifying the values of tilting angle (t) and test force $F_c(t)$ illustrated in Figure 6 in 30 ms time increments for guidance on their application	23
Table 12 -- Number of tests and test samples required to claim compliance with this International Standard	26
Table 13 -- Option for end attachments of specific design	33
Table A.1 -- Magnitudes of resultant reference forces FR_{1x} and FR_{2x}	73
Table C.1 -- Test forces of the proof test of end attachments for test loading level P6 (see 13.2.2.1)	79

Table C.2 -- Test forces for all tests and prescribed number of cycles for the cyclic test, for test loading level P6 (see 16.2, 16.3 and 16.4) 80

Table E.1 -- Contents of ISO/TR 22676 and list of corresponding clauses/subclauses of this International Standard, in which selected items are dealt with 88

Table E.2 -- Possibilities of transposing the top load application point PT for compensation of the dependence of the position of the tilting axis TA of the foot platform on the foot length L 97

Table F.1 -- Correspondence between this International Standard and the essential principles of ISO/TR 16142 98