

ISO 22675:2006-10 (E)

Prosthetics - Testing of ankle-foot devices and foot units - Requirements and test methods

Contents		Page
Foreword		vii
Introduction		viii
1	Scope	1
2	Normative references	2
3	Terms and definitions	2
4	Designations and symbols of test forces	2
5	Strength and related performance requirements and conditions of use	3
6	Coordinate system and test configurations	4
6.1	General	4
6.2	Origin and axes of the coordinate system	4
6.3	Reference points	5
6.4	Test force F	6
6.5	Line of application of test force F	6
6.6	Lines of action of resultant reference forces FR1 and FR2	6
6.7	Longitudinal axis of the foot and effective ankle joint centre	6
6.7.1	General	6
6.7.2	Longitudinal axis of the foot	6
6.7.3	Effective ankle-joint centre, CA	7
7	Test loading conditions and test loading levels	8
7.1	Test loading conditions	8
7.2	Test loading levels	8
8	Values of test forces, dimensions and cycles	9
9	Compliance	16
9.1	General	16
9.2	Particular arrangements and requirements concerning the part required to connect an ankle-foot device or foot unit to the remainder of a prosthetic structure	17
9.2.1	Arrangements for testing	17
9.2.2	Requirements for claiming compliance	17
9.3	Number of tests and test samples required to claim compliance with this International Standard	17
9.4	Multiple use of test samples	18
9.4.1	General	18
9.4.2	Restriction	18
9.5	Testing at particular test loading levels not specified in this International Standard	18
10	Test samples	19
10.1	Selection of test samples	19
10.1.1	General	19
10.1.2	Selection of ankle-foot devices and foot units of appropriate size of foot	19
10.2	Types of test sample	20
10.2.1	Complete structure	20

10.2.2	Partial structure	20
10.3	Preparation of test samples	20
10.4	Identification of test samples	21
10.5	Alignment of test samples	21
10.6	Worst-case alignment position of test samples	21
11	Responsibility for test preparation	23
12	Test submission document	24
12.1	General requirements	24
12.2	Information required for test samples	24
12.3	Information required for tests	25
12.3.1	General	25
12.3.2	For all tests	25
12.3.3	For the static proof test and the static ultimate strength test	25
12.3.4	For the static ultimate strength test	25
12.3.5	For the cyclic test	25
13	Equipment	26
13.1	General	26
13.2	End attachments	26
13.2.1	General	26
13.2.2	Proof test of end attachments	26
13.3	Jig (optional)	28
13.4	Test equipment	28
13.4.1	Test equipment to perform static heel and forefoot loading	28
13.4.2	Test equipment to perform cyclic loading	30
14	Accuracy	37
14.1	General	37
14.2	Accuracy of equipment	37
14.3	Accuracy of procedure	38
15	Test principles	38
15.1	General	38
15.2	Static test procedure	39
15.3	Cyclic test procedure	39
16	Test procedures	39
16.1	Test loading requirements	39
16.1.1	Preparation for test loading	39
16.1.2	Test loading conditions	43
16.2	Static proof test	43
16.2.1	Test method	43
16.2.2	Performance requirement	45
16.2.3	Compliance conditions	45
16.3	Static ultimate strength test	47
16.3.1	Test method	47
16.3.2	Performance requirements	50
16.3.3	Compliance conditions	50
16.4	Cyclic test	52
16.4.1	Test method	52
16.4.2	Performance requirements	54
16.4.3	Compliance conditions	55
17	Test laboratory/facility log	58
17.1	General requirements	58
17.2	Specific requirements	58
18	Test report	58
18.1	General requirements	58
18.2	Specific requirements	59

18.3	Options	59
19	Classification and designation	59
19.1	General	59
19.2	Examples of classification and designation	59
20	Labelling	60
20.1	General	60
20.2	Use of mark "*" and warning symbol	61
20.3	Examples of label layout	61
20.4	Label placement	62
Annex A (informative) Reference data for the specification of the test loading conditions and test loading levels of this International Standard		63
Annex B (informative) Guidance on the application of an alternative static ultimate strength test		71
Annex C (informative) Guidance on the application of an additional test loading level P6		72
Annex D (informative) Summary of the records to be entered in the test laboratory/facility log		74
Annex E (informative) Information on Technical Report ISO/TR 22676 [1]		80
Annex F (informative) Reference to the essential principles of safety and performance of medical devices according to ISO/TR 16142		91
Bibliography		92
Figure 1 -- Coordinate system with reference parameters		5
Figure 2 -- Determination of longitudinal axis of foot (see 6.7.2) and effective ankle-joint centre CA (see 6.7.3)		7
Figure 3 -- Illustration of reference points for the establishment of thresholds listed in Table 10 for specification of the loading profile of the cyclic test		14
Figure 4 -- Illustration of specific set-up of left-sided test sample with top load application point PT 23		
Figure 5 -- Diagrammatic view of test equipment according to 13.4.1 and 13.4.2 with test sample		35
Figure 6 -- Profiles of test force $F_c(t)$ and tilting angle (t) as synchronized functions of time, determining the loading condition of the cyclic test of this International Standard		36
Figure 7 -- Test force $F_c(t)$ of test loading level P5 as function of tilting angle (t) of foot platform		37
Figure 8 -- Preparation for test loading of static test procedure [see 16.1.1 a)]		42
Figure 9 -- Flowchart for the static proof test specified in 16.2.1		46
Figure 10 -- Flowchart for the static ultimate strength test specified in 16.3.1		51
Figure 11 -- Flowchart for the cyclic test specified in 16.4.1 Continued on Figure 12		56
Figure 12 -- Flowchart for the cyclic test specified in 16.4.1 Continued from Figure 11		57
Figure 13 -- General concept for the label layout		60
Figure 14 -- Models for the label layout		61
Figure A.1 -- Illustration of different components of loading		69

Figure A.2 -- Illustration of the dependence of the position of the top load application point PT on the foot length L -- (see A.2.2.3)	70
Figure E.1 -- Effect of f-position of tilting axis TA of foot platform on the elevation E of the foot at the instants of heel contact and toe-off	83
Figure E.2 -- Effect of u-position of tilting axis TA of foot platform on the A/P displacement f of the foot at the instant of toe-off	84
Figure E.3 -- Illustration of the effect of A-P displacement f on the angular movement of the test sample about the top load application point PT	85
Figure E.4 -- Illustration of possibilities of transposing the top load application point PT for compensation of the dependence of the position of the tilting axis TA of the foot platform on the foot length L	88
Figure E.5 -- Illustration of the effect of a fixed compromise offset $u_{TA, C}$ of the tilting axis TA of the foot platform on the A-P displacement f at the foot [see E.3.4.2 c) 2)]	89
Table 1 -- Designations and symbols of test forces	2
Table 2 -- Categories of strength addressed in this International Standard, together with the related performance requirements and test methods for their verification	3
Table 3 -- Test forces and relevant references	9
Table 4 -- Values of bottom offsets $f_{B1, L}$ (heel) and $f_{B2, L}$ (forefoot) for given values of foot length L, relevant to the design and/or adjustment of the rigid foot dummy required to simulate the effective lever arms of an ankle-foot device or foot unit in the proof test of end attachments (see 13.2.2)	10
Table 5 -- Test forces of the proof test of end attachments for test loading levels P5, P4 and P3 (see 13.2.1)	10
Table 6 -- Total length of test samples and segmental lengths of end attachments	11
Table 7 -- Coordinates of top load application point PT and tilting axis TA of foot platform based on given values of foot length L, for all test loading levels	12
Table 8 -- Angles of toe-out position of foot and specific tilting positions of foot platform, for all test loading levels	12
Table 9 -- Test forces for all tests and prescribed number of cycles for the cyclic test, for test loading levels P5, P4 and P3 (see 16.2, 16.3 and 16.4)	13
Table 10 -- Thresholds according to Figure 3 for specification of the application of the loading profile of the cyclic test	15
Table 11 -- Data specifying the values of tilting angle (t) and test force $F_c(t)$ illustrated in Figure 6 in 30 ms time increments for guidance on their application	16
Table 12 -- Number of tests and test samples required to claim compliance with this International Standard	19
Table 13 -- Option for end attachments of specific design	26
Table A.1 -- Magnitudes of resultant reference forces FR_{1x} and FR_{2x}	66
Table C.1 -- Test forces of the proof test of end attachments for test loading level P6 (see 13.2.2.1)	72
Table C.2 -- Test forces for all tests and prescribed number of cycles for the cyclic test, for test loading level P6 (see 16.2, 16.3 and 16.4)	73

Table E.1 -- Contents of ISO/TR 22676 and list of corresponding clauses/subclauses of this International Standard, in which selected items are dealt with 81

Table E.2 -- Possibilities of transposing the top load application point PT for compensation of the dependence of the position of the tilting axis TA of the foot platform on the foot length L 90

Table F.1 -- Correspondence between this International Standard and the essential principles of ISO/TR 16142 91