

DIN EN 14236:2008-06 (E)

Ultrasonic domestic gas meters

Contents		Page
Foreword		7
1	Scope	8
2	Normative references	8
3	Terms, definitions and symbols	10
3.1	Terms and definitions	10
3.2	Symbols	13
4	Normal operating conditions	14
4.1	Flow range	14
4.2	Maximum working pressure	15
4.3	Temperature range	15
4.4	Range of gases	16
4.4.1	Test gases	16
4.5	Orientation	16
5	Metrological performance	16
5.1	General	16
5.2	Mode comparison	17
5.2.1	General	17
5.2.2	Requirements	17
5.2.3	Test	17
5.3	Permissible errors	17
5.3.1	Requirements	17
5.3.2	Test	17
5.4	Gas -- air relationship	18
5.4.1	General	18
5.4.2	Requirements	18
5.4.3	Test	19
5.5	Pressure absorption	19
5.5.1	Requirements	19
5.5.2	Test	19
5.6	Metrological stability	20
5.6.1	Requirements	20
5.6.2	Test	20
5.7	Immunity to contaminants in gas stream	20
5.7.1	Requirements	20
5.7.2	Test	20
5.7.3	Specification of contamination dust	22
5.8	Installation effects	22
5.8.1	Requirements	22
5.8.2	Test	22
5.9	Zero flow	22
5.9.1	Requirements	22
5.9.2	Test	22
5.10	Reverse flow	23
5.10.1	Requirements	23
5.10.2	Test	23
5.11	Low flow registration	23
5.11.1	Requirement	23

5.11.2	Test	23
5.12	High flow registration	23
5.12.1	Requirement	23
5.12.2	Test	23
5.13	Pulsed (unsteady) flow	23
5.13.1	General	23
5.13.2	Requirements	24
5.13.3	Test	24
5.14	Temperature sensitivity	25
5.14.1	Requirements	25
5.14.2	Test	25
6	Construction and materials	25
6.1	General	25
6.2	Robustness of meter case	26
6.2.1	General	26
6.2.2	Protection against penetration of dust and water	26
6.2.3	Resistance to internal pressure	26
6.2.4	External leak tightness	26
6.2.5	Heat resistance	27
6.2.6	Connections	27
6.2.7	Resistance to vibration	30
6.2.8	Resistance to impact	32
6.2.9	Resistance to mishandling	34
6.3	Corrosion protection	35
6.3.1	General	35
6.3.2	Protection against external corrosion for material which is not corrosion resistant	35
6.3.3	Protection against external corrosion for corrosion resistant material	37
6.3.4	Protection against internal corrosion for material which is not corrosion resistant	38
6.3.5	Protection against internal corrosion for corrosion resistant material	40
6.4	Casework decorative finish	40
6.4.1	Scratch test	40
6.4.2	Humidity	41
6.5	Ageing of non-metallic casework	41
6.5.1	Requirements	41
6.5.2	Test	41
6.6	Ageing of external surfaces of the meter, including index windows and adhesion of the index window	41
6.6.1	Requirements	41
6.6.2	Test	42
6.7	Protection against solar radiation	42
6.7.1	Requirements	42
6.7.2	Test	42
6.8	Resistance to external humidity	42
6.8.1	Requirements	42
6.8.2	Test	43
6.9	Flame retardance of external surfaces	43
6.9.1	Requirements	43
6.9.2	Test	43
6.10	Resistance to storage temperature range	43
6.10.1	Requirement	43
6.10.2	Test	43
6.11	Resistance to the effects of toluene/iso-octane vapour	44
6.11.1	Requirements	44
6.11.2	Test	44
6.12	Resistance to water vapour	47
6.12.1	Requirements	47
6.12.2	Test	47
6.13	Ageing	48
6.13.1	Requirements	48
6.13.2	Test	49

7	Optional features	49
7.1	Pressure measuring point	49
7.1.1	Requirements	49
7.1.2	Test	49
7.2	Resistance to high ambient temperature	49
7.2.1	Requirements	49
7.2.2	Test	50
7.2.3	Meter fitted with a thermal shut-off valve	51
7.3	Meters with temperature conversion	51
7.4	Ancillary devices (if fitted)	51
7.4.1	Requirement	51
7.4.2	Test	52
7.5	Use in hazardous zones	52
8	Index	52
8.1	Recording and storage	52
8.1.1	Requirement	52
8.1.2	Test	52
8.2	Display	52
8.2.1	Requirement	52
8.2.2	Test	52
8.3	Segmental display	53
8.3.1	Requirements	53
8.3.2	Test	53
8.4	Non-volatile memory	53
8.4.1	Requirements	53
8.4.2	Test	53
8.5	Display reset	54
8.5.1	Requirements	54
8.5.2	Test	54
9	Marking	54
9.1	All meters	54
9.2	Two-pipe meters	55
9.2.1	Requirements	55
9.2.2	Test	55
9.3	Durability and legibility of marking	55
9.3.1	Requirements	55
9.3.2	Weathering	55
9.3.3	Indelibility test	56
9.4	Accompanying information	56
10	Software	57
10.1	Requirements	57
10.2	Test	57
11	Communications	57
11.1	General	57
11.2	Character transmission	58
11.3	Communications protocol	58
11.3.1	General	58
11.3.2	Wakeup	58
11.3.3	Sign-off	58
11.3.4	Security	58
11.3.5	Time-outs	58
11.4	Data	58
11.4.1	General	58
11.4.2	Data read-out mode	59
11.5	Test-mode	59
11.5.1	General	59
11.5.2	Test-mode commands	59
11.5.3	Response of meter to test commands	59

11.6	Data optical port	61
11.7	Galvanic port (optional)	61
11.8	Diagnostics	61
11.8.1	General	61
11.8.2	Displayed flags	61
12	Battery	62
12.1	General	62
12.2	Voltage interruptions	62
12.2.1	Requirements	62
12.2.2	Test	62
12.3	Minimum operating voltage	63
12.3.1	Requirements	63
12.3.2	Test	63
12.4	Battery life	63
12.4.1	Requirements	63
12.4.2	Test	63
13	Immunity to electromagnetic disturbances	63
13.1	General	63
13.2	Electrostatic discharge	63
13.2.1	Requirements	63
13.2.2	Test	63
13.3	Radio frequency electromagnetic field	64
13.3.1	Requirements	64
13.3.2	Test	64
13.4	Electromagnetic induction (power frequency)	64
13.4.1	Requirements	64
13.4.2	Test	65
13.5	Electromagnetic induction (pulsed field)	65
13.5.1	Requirements	65
13.5.2	Test	65
13.6	Radio interference suppression	65
13.6.1	Requirements	65
13.6.2	Test	65
14	Ultrasonic (acoustic) noise interference	65
14.1	Requirements	65
14.2	Test	66
14.2.1	Test sequence	66
14.2.2	White noise test	66
14.2.3	Scanning frequency test	66
15	Meters supplied for testing	67
Annex A (informative) Test gases		69
A.1	General	69
A.2	Test gas properties	69
Annex B (normative) Production requirements for gas meters		70
B.1	Specification	70
B.2	Technical requirements	70
B.3	Certificates of conformity	70
Annex C (normative) Meters with gas temperature conversion devices		72
C.1	Scope	72
C.2	Metrological performance	72
C.2.1	Errors of indication	72

C.2.2	Error of indication where the temperature of the gas at the meter inlet is significantly different from the ambient temperature of the air surrounding the meter	75
C.2.3	Temperature sensitivity	77
C.2.4	Temperature converted volume	77
	Annex ZA (informative)	78
	Bibliography	82