

DIN EN 13785:2010-05 (E)

Regulators with a capacity of up to and including 100 kg/h, having a maximum nominal outlet pressure of up to and including 4 bar, other than those covered by EN 12864 and their associated safety devices for butane, propane or their mixtures (includes Amendment A1:2008)

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 3.1 | General terms and definitions | 7 |
| 3.2 | Terms and definitions concerning gas | 10 |
| 3.3 | Terms and definitions concerning pressures | 10 |
| 3.4 | Terms and definitions concerning rates | 11 |
| 4 | Types of regulators | 11 |
| 4.1 | Introduction | 11 |
| 4.2 | Regulators for installations where the final regulator supplies a pressure specified in EN 437 | 12 |
| 4.3 | Other regulators | 12 |
| 5 | Constructional characteristics | 12 |
| 5.1 | General | 12 |
| 5.2 | Materials | 13 |
| 5.3 | Special requirements | 16 |
| 5.3.1 | Pressure sensing subassembly | 16 |
| 5.3.2 | Regulation subassembly | 16 |
| 5.3.3 | Back pressure subassembly | 16 |
| 5.3.4 | Connection subassembly | 17 |
| 5.4 | Mechanical strength | 19 |
| 5.4.1 | Resistance to impact | 19 |
| 5.4.2 | Resistance to pressure | 19 |
| 5.4.3 | Strength of connections | 20 |
| 5.5 | Soundness | 21 |
| 5.6 | Mechanical endurance | 22 |
| 5.6.1 | General requirements | 22 |
| 5.6.2 | Special requirements | 22 |
| 5.7 | Resistance to humidity changes | 22 |
| 5.8 | Resistance to corrosion | 22 |
| 6 | Performance characteristics | 23 |
| 6.1 | General | 23 |
| 6.1.1 | Introduction | 23 |
| 6.1.2 | Supply pressure | 23 |
| 6.1.3 | Regulated pressure | 23 |
| 6.2 | Supply pressure and regulated pressure according to 4.2 | 24 |
| 6.2.1 | Single stage fixed regulator for EN 437 pressures | 24 |
| 6.2.2 | Two stages fixed or adjustable regulators for EN 437 pressures | 24 |
| 6.2.3 | Three stages fixed or adjustable regulators for EN 437 pressures | 25 |
| 6.3 | Variable regulators | 27 |
| 6.4 | Regulators out of the pressures of EN 437 | 27 |

| | | |
|---|---|-----------|
| 7 | Test methods | 28 |
| 7.1 | General conditions | 28 |
| 7.1.1 | Type of test gas | 28 |
| 7.1.2 | Test conditions | 28 |
| 7.1.3 | Equivalence formulas | 28 |
| 7.1.4 | Test samples | 29 |
| 7.2 | Verification of constructional characteristics | 29 |
| 7.2.1 | Resistance to impact | 29 |
| 7.2.2 | Resistance to pressure | 29 |
| 7.2.3 | Mechanical strength of connections | 30 |
| 7.2.4 | Regulation subassembly | 34 |
| 7.2.5 | Soundness | 34 |
| 7.2.6 | Mechanical endurance | 35 |
| 7.2.7 | Resistance to humidity changes | 36 |
| 7.2.8 | Resistance to corrosion | 37 |
| 7.3 | Verification of performance characteristics | 37 |
| 7.3.1 | General | 37 |
| 7.3.2 | Plotting of the performance curves | 40 |
| 8 | Marking, packaging, instructions | 40 |
| 8.1 | General | 40 |
| 8.2 | Marking of the regulator | 40 |
| 8.3 | Packaging | 41 |
| 8.4 | Instructions for installation, use and maintenance | 41 |
| Annex A (normative) Special requirements for regulators fitted with pressure or rate operated safety devices | | 42 |
| A.1 | Regulators fitted with an over-pressure relief | 42 |
| A.1.1 | Definition | 42 |
| A.1.2 | Constructional characteristics | 42 |
| A.1.3 | Performance characteristics | 42 |
| A.1.4 | Test methods | 43 |
| A.1.5 | Regulator marking | 43 |
| A.2 | Regulators fitted with an over-pressure shut off safety valve | 43 |
| A.2.1 | Definition | 43 |
| A.2.2 | Constructional characteristics | 43 |
| A.2.3 | Performance characteristics | 44 |
| A.2.4 | Test methods | 44 |
| A.3 | Regulators fitted with an under-pressure shut off safety device | 45 |
| A.3.1 | Definition | 45 |
| A.3.2 | Constructional and performance characteristics | 45 |
| A.3.3 | Test methods | 46 |
| A.4 | Regulators fitted with an excess flow valve | 46 |
| A.4.1 | Definition | 46 |
| A.4.2 | Performance characteristics | 46 |
| A.4.3 | Test methods | 46 |
| A.4.4 | User and maintenance instructions | 47 |
| A.5 | Regulators fitted with a regulated pressure limiter | 47 |
| A.5.1 | Definition | 47 |
| A.5.2 | Constructional and performance characteristics | 47 |
| A.5.3 | Test methods | 48 |
| A.5.4 | User and maintenance instructions | 48 |
| Annex B (normative) Special requirements for regulators fitted with a thermal cut out | | 49 |
| B.1 | Definition | 49 |
| B.2 | Constructional characteristics | 49 |
| B.3 | Performance characteristics | 49 |
| B.4 | Test methods | 49 |

| | |
|---|--|
| Annex C (normative) Special requirements for low pressure regulators under extreme temperature conditions (temperatures below -20 °C) | 51 |
| Annex D (normative) Method for measuring leaks at test pressures less than or equal to 16 bar | 52 |
| D.1 | Scope 52 |
| D.2 | Diagram of the test bench 52 |
| D.3 | Coefficient K 53 |
| D.3.1 | Method 53 |
| D.3.2 | Calculations 53 |
| D.4 | Measurement of the leak 53 |
| D.4.1 | Method 53 |
| D.4.2 | Calculations 53 |
| D.5 | Checks 54 |
| Annex E (normative) Complementary test requirements for non metallic thermoplastic or thermal setting materials used in the construction of regulators | 55 |
| E.1 | Scope 55 |
| E.2 | Materials 55 |
| E.3 | Special conditions for carrying out the tests mentioned in the body of the document 55 |
| E.3.1 | Resistance to impact (see 5.4.1 and 7.2.1) 55 |
| E.3.2 | Mechanical resistance of connections (see 5.4.3 and 7.2.3) 55 |
| E.3.3 | Soundness (see 5.5 and 7.2.5) 56 |
| E.4 | Special requirements 56 |
| E.4.1 | Resistance to hydrocarbons 56 |
| E.4.2 | Resistance to cracking under stress and when chemical agents are present 56 |
| E.4.3 | Characteristics relating to fire resistance 56 |
| E.4.4 | Accelerated ageing 57 |
| E.5 | Sampling and order of tests 57 |
| Annex F (normative) Requirements for elastomeric reinforced diaphragms | 58 |
| Annex G (normative) Inlet connections | 59 |
| Annex H (normative) Outlet connections | 106 |
| Annex I (informative) Test method for resistance to corrosion | 136 |
| I.1 | Principle 136 |
| I.2 | Reagents 136 |
| I.2.1 | Saline solution 136 |
| I.2.2 | Compressed air 136 |
| I.2.3 | Salt mist 137 |
| I.3 | Apparatus 137 |
| I.3.1 | Spraying chamber 137 |
| I.3.2 | Sprayers 137 |
| I.3.3 | Heating device 138 |
| I.3.4 | Salt solution supply device 138 |
| I.3.5 | Compressed air supply device 138 |
| I.3.6 | Mist collectors 138 |
| I.4 | Test method 139 |
| I.4.1 | Method of exposure of regulators 139 |
| I.4.2 | Duration of tests 139 |
| I.4.3 | Checks 139 |
| I.4.4 | Cleaning of regulators 139 |
| I.5 | Results 139 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 90/396/EEC | 142 |
| Bibliography | 144 |