

DIN EN 15069:2010-07 (E)

Safety gas connection valves for metal hose assemblies used for the connection of domestic appliances using gaseous fuel

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | 5 |
| Introduction | | 6 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | General requirements | 9 |
| 4.1 | SC valve types | 9 |
| 4.2 | Classification | 10 |
| 4.2.1 | Temperature classes | 10 |
| 4.2.2 | Pressure classes | 10 |
| 4.3 | Construction requirements | 10 |
| 4.3.1 | General | 10 |
| 4.3.2 | Materials | 11 |
| 4.3.3 | Nominal sizes | 11 |
| 4.4 | Construction | 11 |
| 4.5 | Connection | 12 |
| 4.5.1 | General | 12 |
| 4.5.2 | Connection and disconnection | 12 |
| 4.5.3 | Disconnection | 12 |
| 4.5.4 | Rotation | 12 |
| 4.6 | Operation | 12 |
| 4.6.1 | General | 12 |
| 4.6.2 | Manual operated control (if fitted) | 12 |
| 4.7 | Dangerous substances | 12 |
| 5 | Performance requirements and tests | 13 |
| 5.1 | General | 13 |
| 5.2 | Test end fittings | 13 |
| 5.3 | Test sequence schedule | 13 |
| 5.4 | Leak-tightness | 15 |
| 5.4.1 | Angular seal | 15 |
| 5.4.2 | External leak-tightness | 15 |
| 5.4.3 | Internal leak-tightness | 16 |
| 5.5 | Internal Pressure | 16 |
| 5.5.1 | Requirements | 16 |
| 5.5.2 | Test | 17 |
| 5.6 | Rated flow rate | 17 |
| 5.6.1 | Requirements | 17 |
| 5.6.2 | Test | 17 |
| 5.7 | Tensile strength resistance | 19 |
| 5.7.1 | Requirements | 19 |
| 5.7.2 | Tests | 19 |
| 5.8 | Bending resistance | 20 |
| 5.8.1 | Requirements | 20 |
| 5.8.2 | Tests | 20 |
| 5.9 | Resistance to torsion | 20 |

| | | |
|--------|---|----|
| 5.9.1 | Requirements | 20 |
| 5.9.2 | Tests | 20 |
| 5.10 | Resistance to impact | 21 |
| 5.10.1 | Requirements | 21 |
| 5.10.2 | Tests | 21 |
| 5.11 | Durability | 22 |
| 5.11.1 | Durability of the manually operated control SC valve | 22 |
| 5.11.2 | Durability of connection and disconnection | 23 |
| 5.11.3 | Rotation durability of the SC valve outlet | 23 |
| 5.11.4 | Temperature durability - Thermal ageing | 23 |
| 5.12 | High and low temperature resistance | 24 |
| 5.12.1 | Low temperature resistance | 24 |
| 5.12.2 | High temperature resistance (only for SC valve without TSD) | 26 |
| 5.12.3 | Leak-tightness during thermal load (only for SC valve with TSD) | 26 |
| 5.13 | Resistance to lubricants | 26 |
| 5.13.1 | General | 26 |
| 5.13.2 | Requirement | 26 |
| 5.13.3 | Test | 26 |
| 5.14 | Reaction to fire | 27 |
| 5.14.1 | Requirement | 27 |
| 5.14.2 | Testing and assessment methods | 27 |
| 5.15 | Resistance to gas | 27 |
| 5.15.1 | General | 27 |
| 5.15.2 | Requirement | 27 |
| 5.15.3 | Test | 27 |
| 5.16 | Corrosion resistance | 28 |
| 5.16.1 | Requirement | 28 |
| 5.16.2 | Test | 28 |
| 5.17 | Operating torque for a manually operated control SC valve | 28 |
| 5.17.1 | Requirement | 28 |
| 5.17.2 | Test | 28 |
| 5.18 | Operating strength for a safety quick connection SC valve | 29 |
| 5.18.1 | Requirement | 29 |
| 5.18.2 | Test | 29 |
| 5.19 | Stop resistance | 29 |
| 5.19.1 | Requirement | 29 |
| 5.19.2 | Test | 30 |
| 5.20 | SC valves type 2 and 4 | 30 |
| 5.20.1 | Leak-tightness of the OSD | 30 |
| 5.20.2 | Overflow safety rate | 30 |
| 5.20.3 | Overflow safety durability | 31 |
| 5.20.4 | Normal flow durability | 31 |
| 5.21 | Electrical continuity | 32 |
| 5.21.1 | Requirement | 32 |
| 5.21.2 | Test | 32 |
| 5.22 | Leak-tightness of the system with non-metal components | 32 |
| 5.22.1 | Requirement | 32 |
| 5.22.2 | Test | 32 |
| 5.23 | SC valves type 3 and 4 | 33 |
| 5.23.1 | Reaction to temperature | 33 |
| 6 | Evaluation of conformity | 33 |
| 6.1 | General | 33 |
| 6.2 | Type testing | 33 |
| 6.2.1 | Initial type testing (ITT) | 33 |
| 6.2.2 | Subsequent type testing | 34 |
| 6.3 | Factory production control (FPC) | 34 |
| 6.3.1 | General | 34 |
| 6.3.2 | FPC requirements for all manufacturers | 34 |
| 6.3.3 | Manufacturer-specific FPC system requirements | 36 |
| 6.4 | Installation instructions | 37 |
| 6.5 | Packaging | 38 |

| | |
|--|-----------|
| Annex A (informative) SC valve and hose fitting design requirements for connection to the gas supply pipework or to the pressure reduction device of portable gas bottles | 39 |
| Annex B (informative) Test end fitting | 58 |
| Annex ZA (informative) Clauses of this European Standard addressing the provision of the EU Construction Products Directive | 59 |
| ZA.1 Scope and relevant characteristics | 59 |
| ZA.2 Procedure for attestation of conformity of SC valves | 60 |
| ZA.2.1 System of attestation of conformity | 60 |
| ZA.2.2 EC Certificate and Declaration of conformity | 63 |
| ZA.3 CE marking and labeling | 64 |
| Bibliography | 66 |