ISO 26142:2010-06 (E)

Hydrogen detection apparatus - Stationary applications

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 General requirements 4
4.1 Construction 4
4.1.1 General 4
4.1.2 Enclosure 4
4.1.3 Measuring range 4
4.1.4 Alarm system 4
4.1.5 Indicators 5
4.1.6 Adjustments 5
4.1.7 Software-controlled hydrogen detection apparatus 6
4.1.8 Reliability 7
4.2 Labelling and marking 8
4.3 Instruction manual 8
4.4 Vibration 9

5 Performance requirements 9

6 Tests 9
6.1 General requirements for tests 9
6.1.1 Number of samples 9
6.1.2 Sequence of tests 9
6.1.3 Preparation of the hydrogen detection apparatus before testing 10
6.2 Test equipment 10
6.3 Normal test conditions 10
6.3.1 Temperature 10
6.3.2 Pressure 10
6.3.3 Humidity 10
6.3.4 Voltage 10
6.3.5 Orientation 10
6.4 Test methods 11
6.4.1 General 11
6.4.2 Standard response test 11
6.4.3 Measuring range and calibration 11
6.4.4 Stability 12
6.4.5 Alarm set point(s) 13
6.4.6 Temperature 13
6.4.7 Pressure 14
6.4.8 Humidity 14
6.4.9 Vibration 14
6.4.10 Orientation 15
6.4.11 Flow rate for aspirated apparatus 16
6.4.12 Air velocity 16
6.4.13 Time of response and time of recovery 17

6.4.14 Selectivity 17
6.4.15 Poisoning 17
6.4.16 Operation above the measuring range 18
6.4.17 Power supply variations 18
6.4.18 Power supply interruptions, voltage transients and step changes of voltage 19
6.4.19 Warm-up time after restart 19
6.4.20 Electromagnetic immunity 19
6.4.21 Field calibration kit 20

Annex A (informative) Chamber test method 21

Annex B (informative) Flow-through test method 24

Bibliography 27