

DIN EN 12405-3:2016-04 (E)

Gas meters - Conversion devices - Part 3: Flow computer

Contents		Page
European foreword		5
Introduction		6
1	Scope	8
2	Normative references	8
3	Terms, definitions and symbols	10
3.1	Terms and definitions	10
3.2	Symbols and subscripts	16
3.3	Abbreviations	18
3.4	Environmental classification for flow computers	18
3.4.1	Climatic conditions	18
3.4.2	Mechanical conditions	18
3.4.3	Electrical and Electromagnetic conditions	18
4	Principle of measurement	18
4.1	General	18
4.2	Correction functions	19
4.2.1	General	19
4.2.2	Correction of the volume at measurement conditions	20
4.2.3	Temperature and pressure correction of USM body dimension	23
4.2.4	Temperature and pressure measurement correction for conversion	23
5	Rated operating conditions	23
5.1	Specified field of measurement	23
5.1.1	General	23
5.1.2	Specified measurement range for gas pressure	23
5.1.3	Specified measurement range for gas temperature	24
5.1.4	Gas characteristics	24
5.1.5	Base conditions	24
5.2	Environmental conditions	24
5.2.1	Ambient temperature range	24
5.2.2	Humidity range	24
5.3	Power supply	24
6	Construction requirements	25
6.1	General	25
6.2	Sealing	25
6.3	Time measuring functions	27
6.3.1	Clock	27
6.3.2	Time interval	27
6.4	Casings	28
6.5	Indications	28
6.5.1	General	28
6.5.2	Electronic indicating device	30
6.6	Inputs for volume conversion	30
6.7	Alarms in flow computer	31
6.7.1	Detection of defective operation situations	31
6.7.2	Handling of volumes during maintenance	31
6.7.3	Memorization of metrological data	31

6.7.4	Handling of alarms	31
6.8	Specific monitoring functions performed by flow computer	31
6.8.1	General	31
6.8.2	Turbine Meter health check (Mechanical meter)	33
6.8.3	USM health check (meter integrity check)	34
6.8.4	Gas analysis devices health check	35
6.8.5	p-T transducer health check	36
6.8.6	Self check of the Z algorithm	36
6.8.7	Volume comparison	36
6.8.8	Gas quality comparison	38
6.9	Cut-off function	38
6.10	Long-term data storage	38
6.10.1	General	38
6.10.2	Categories of data to be stored	39
6.10.3	Triggers and methods for storage	39
6.10.4	Clock-time stamps	40
6.10.5	Security (physical, electronic and software)	40
6.10.6	Error handling	41
6.10.7	Long term data storage - Security audit	41
7	Installation requirements	42
7.1	General	42
7.2	Calculator	43
7.3	Temperature transducer	43
7.4	Pressure transducer	43
8	Performance	44
8.1	Reference conditions	44
8.2	Rated operating conditions	44
8.3	Maximum permissible errors	44
8.3.1	General	44
8.3.2	Global approach: error of main indication	45
8.3.3	Modular approach: specific errors for a FC	45
8.4	Conditions of matching the constituent elements of a FC	45
8.5	Influence factors	46
8.6	Disturbances	46
8.7	Durability	46
8.8	Repeatability	46
8.9	Reliability	46
8.10	Adjustment and calibration of the transducers	47
9	Tests of conformity	47
9.1	Verification of the construction requirements	47
9.2	Verification of the performance requirements	48
9.2.1	Test conditions	48
9.2.2	Samples of FC required for testing	49
10	Marking	50
11	Installation and operating instructions	51
Annex A (normative)	Type test	52
A.1	General conditions	52
A.2	Accuracy tests under reference conditions	54
A.3	Effect of ambient temperature	55
A.4	Effect of damp heat, steady-state test	55
A.5	Effect of damp heat, cyclic test	56
A.6	Electrical power variation	56
A.7	Short time power reductions	57
A.8	Electrical bursts	58
A.9	Electromagnetic susceptibility	58

A.10	Electrostatic discharges	59
A.11	Overload of pressure (only for pressure transducers)	59
A.12	Effect of vibrations	60
A.13	Effect of shocks	60
A.14	Overload of pressure (mechanical) (only for pressure transducer)	61
A.15	Durability	61
A.16	Alarms operation	62
A.17	Repeatability	63
A.18	Short time DC power variations	63
A.19	Surges on supply lines and/or signal lines	64
A.20	Power frequency magnetic field	64
Annex B (normative) Pressure transducers		65
B.1	Scope	65
B.2	Rated operating conditions	65
B.3	Construction requirements	65
B.4	Performances	66
B.5	Tests of conformity	67
B.6	Marking	67
Annex C (normative) Temperature transducers		68
C.1	Scope	68
C.2	Rated operating conditions	68
C.3	Construction requirements	68
C.4	Performances	69
C.5	Tests of conformity	70
C.6	Marking	70
Annex D (normative) Requirements and testing of meter error correction		71
D.1	General	71
D.2	Verification of the volumetric flow rate determination	71
D.3	Verification of the gas density calculation procedure	71
D.4	Verification of the gas viscosity calculation procedures	72
D.5	Verification of the error transposition from $e(Q_i)$ to $e(Re_i)$	72
D.6	Verification of the error function (Q) or (Re) interpolation or approximation	73
D.7	Verification of correction factor $F(Q)$ or $F(Re)$, corrected flow rate and corrected volume determination	73
D.8	Verification of the activation and deactivation of error correction calculations on limits of its application	73
Annex E (informative) Range of application of meter error correction with functions: $e(Q)$ or $e(Re)$.		74
E.1	General	74
E.2	Range of application	74
E.3	Example for turbine meters working at pop nearly constant	75
Bibliography		77