

DIN EN 14236:2018-12 (E)

Ultrasonic domestic gas meters

Contents		Page
European foreword		5
1	Scope	6
2	Normative references	6
3	Terms, definitions and symbols	8
3.1	Terms and definitions	8
3.2	Symbols	11
4	Normal operating conditions	13
4.1	Flow range	13
4.2	Maximum working pressure	13
4.3	Temperature range	13
4.4	Range of gases	14
4.5	Orientation	14
5	Metrological performance	14
5.1	General	14
5.2	Mode comparison	15
5.3	Permissible errors	15
5.4	Gas -- air relationship	16
5.5	Pressure absorption	17
5.6	Metrological stability	18
5.7	Immunity to contaminants in gas stream	18
5.8	Installation effects	20
5.9	Zero flow	20
5.10	Reverse flow	20
5.11	Low flow registration	21
5.12	High flow registration	21
5.13	Pulsed (unsteady) flow	21
5.14	Temperature sensitivity	22
6	Construction and materials	23
6.1	General	23
6.2	Robustness of meter case	23
6.3	Corrosion protection	32
6.4	Casework decorative finish	38
6.5	Ageing of non-metallic casework	38
6.6	Ageing of external surfaces of the meter, including index windows and adhesion of the index window	39
6.7	Protection against solar radiation	39
6.8	Resistance to external humidity	40
6.9	Flame retardance of external surfaces	41
6.10	Resistance to storage temperature range	41
6.11	Resistance to the effects of toluene/iso-octane vapour	41
6.12	Resistance to water vapour	44
6.13	Ageing	45
7	Optional features	46
7.1	Pressure measuring point	46

B.3	Certificates of conformity	67
	Annex C (normative) Meters with gas temperature conversion devices	69
C.1	Scope	69
C.2	Metrological performance	69
	Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2014/32/EU Measuring Instruments Directive aimed to be covered	73
	Bibliography	79