ISO 19882:2018 (E)

Gaseous hydrogen — Thermally activated pressure relief devices for compressed hydrogen vehicle fuel containers

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Service conditions

4.1 General
4.2 Design service life
4.3 Nominal working pressure
4.4 Durability test cycles
4.5 Temperature range

5 Quality assurance

6 General requirements

6.1 Material requirements
6.2 Design requirements
6.3 Flow capacity
6.4 Rework and repair
6.5 Failure modes and effects analysis (FMEA)

7 Design qualification testing

7.1 General
7.2 Pressure cycling
7.2.1 Sampling
7.2.2 Procedure
7.2.3 Acceptable results
7.3 Accelerated life
7.3.1 Sampling
7.3.2 Procedure
7.3.3 Acceptable results
7.4 Thermal cycling
7.4.1 Sampling
7.4.2 Procedure
7.4.3 Acceptable results
7.5 Accelerated cyclic corrosion
7.5.1 Sampling
7.5.2 Procedure
7.5.3 Acceptable results
7.6 Automotive fluids exposure
7.6.1 Sampling
7.6.2 Procedure
7.6.3 Acceptable results
7.7 Atmospheric exposure test
7.7.1 General
7.7.2 Oxygen aging
7.7.2.1 Sampling
7.7.2.2 Procedure

7.7.2.3 Acceptable results
7.7.3 Ozone
7.7.3.1 Sampling
7.7.3.2 Procedure
7.7.3.3 Acceptable results
7.8 Stress corrosion cracking resistance
7.8.1 Sampling
7.8.2 Procedure
7.8.3 Acceptable results
7.9 Impact due to drop and vibration
7.9.1 Impact due to drop
7.9.1.1 Sampling
7.9.1.2 Procedure
7.9.1.3 Acceptable results
7.9.2 Vibration
7.9.2.1 Sampling
7.9.2.2 Procedure
7.9.2.3 Acceptable results
7.10 Leakage
7.10.1 Sampling
7.10.2 Procedure
7.10.3 Acceptable results
7.11 Bench top activation
7.11.1 Sampling
7.11.2 Procedure
7.11.3 Acceptable results
7.12 Flow capacity
7.12.1 Sampling
7.12.2 Procedure
7.12.3 Acceptable results
7.13 High pressure activation and flow
7.13.1 Sampling
7.13.2 Procedure
7.13.3 Acceptable results

8 Inspection and acceptance testing

8.1 Inspection and acceptance testing plan
8.2 Inspector’s responsibilities
8.3 Inspection of system critical components
8.4 Leak testing

9 Production batch testing

9.1 General
9.2 Production batch sizes
9.2.1 General
9.2.2 Fusible materials
9.2.3 Pressure relief devices
9.3 Pressure relief device components
9.4 Thermal activation verification
9.4.1 General
9.4.2 High temperature soak
9.4.3 Activation
9.5 Pressure cycle verification
9.5.1 General
9.5.2 Procedure
9.5.3 Acceptable results

10 Marking

10.1 Required information
10.2 Marking methods

11 Component literature

Annex A (informative) Subsystem and vehicle level considerations

A.1 Purpose
A.2 Design service life
A.3 Design nominal working pressure
A.4 External environment
A.4.1 Location of pressure relief devices
A.4.2 Pressure relief device cautionary labelling
A.4.3 Pressure relief device discharge vent and leakage capture systems
A.4.3.1 General
A.4.3.2 Pressure relief device discharge vent system vent line materials of construction
A.4.3.3 Pressure relief device discharge vent system routing
A.4.3.4 Pressure relief device discharge vent system intrusion
A.4.3.5 Leakage capture systems (boxes/housings)
A.4.3.6 Fuel storage system barriers/shields
A.4.3.7 Pressure relief device pressure connections
A.5 Flow capacity
A.6 In-service conditions
A.6.1 Inspection
A.6.2 Rework and repair
A.6.3 Replacement
A.6.4 Reuse and reinstallation
A.6.5 Destroyed

Annex B (informative) Design qualification test rationale

B.1 Pressure cycling test
B.2 Accelerated life test
B.3 Thermal cycling test
B.4 Accelerated cyclic corrosion test
B.5 Automotive fluid exposure test
B.6 Atmospheric exposure test
B.7 Stress corrosion cracking resistance test
B.8 Impact due to drop and vibration test
B.9 Leakage test
B.10 Benchtop activation test
B.11 Flow capacity test
B.12 High pressure activation and flow test

Page count: 28