DIN EN 26:2024-04 (E)

Gas-fired instantaneous water heaters for the production of domestich ot water

Contents

Page

European foreword 8

1 Scope 9

2 Normative references 9

3 Terms and definitions 12

4 Classification 28
4.1 Gases and appliance categories 28
4.2 Mode of air supply and evacuation of the combustion products 28
4.3 Water pressure 28

5 Constructional requirements 28
5.1 Conversion to different gases 28
5.1.1 General 28
5.1.2 Permissible operations for changing gases 29
5.2 Materials 29
5.2.1 General requirements related to the use of materials in water heaters 29
5.2.2 Materials in contact with water for human consumption 30
5.2.3 Durability against corrosion of combustion product evacuation duct 31

Table 1 -- Metallic flue duct material specifications 32
5.2.4 Disassembly, recycling and disposal 32
5.2.5 Design - Assembly - Strength 33
5.2.6 Accessibility - Ease of maintenance - Fitting and removal 33
5.2.7 Connection to gas and water pipes 33
5.2.8 Soundness 34
5.2.9 Supply of combustion air and evacuation of the combustion products 35
5.2.10 Checking the state of operation 39
5.2.11 Drainage 39
5.2.12 Electrical and electromagnetic safety 39
5.2.13 Operational safety in the event of failure of the auxiliary energy 40
5.3 Adjusting, control and safety devices 41
5.3.1 General 41
5.3.2 Shut off valves and/or gas rate adjusters 41
5.3.3 Preset gas rate adjusters 42
5.3.4 Gas pressure regulator 43
5.3.5 Pressure test points 43
5.3.6 Automatic water-operated gas valve 43
5.3.7 Ignition devices 43
5.3.8 Flame supervision device 44
5.3.9 Atmosphere sensing device for type AAS appliances 45
5.3.10 Combustion products discharge safety device for type B11BS, B12BS and B13BS appliances 46
5.3.11 Protection against accidental overheating of thermostatic appliances 46
5.3.12 Composition of the gas circuit 46
5.3.13 Protection for appliances intended to be installed in a partially protected place 47
5.4 Main burner 47
5.5 Supplementary requirements for condensing water heaters 48
5.5.1 Materials in contact with condensate 48
5.5.2 Discharge of condensate 48

5.5.3 Control of the combustion products temperature 48
5.5.4 Chemical composition of the condensate 49

6 Operational requirements 49
6.1 General 49
6.1.1 Introduction 49
6.1.2 Characteristics of the test gases 49
6.1.3 Requirements for preparation of the test gases 49
6.1.4 Choice of test gases 49
6.1.5 Test pressures 49
6.1.6 General test conditions 49
6.2 Soundness 54
6.2.1 Soundness of the gas circuit 54
6.2.2 Soundness of the combustion circuit and evacuation of the combustion products 55

Table 2 -- Maximum admissible leakage rates 57
6.2.3 Soundness of the water circuit 61
6.3 Heat inputs 61
6.3.1 General 61
6.3.2 Nominal heat input 63
6.3.3 Minimum heat input 64
6.4 Temperature of the control knobs 64
6.4.1 Requirements 64
6.4.2 Test 64
6.5 Temperature of the adjusting, control and safety devices 64
6.5.1 Requirement 64
6.5.2 Test 64
6.6 Temperature of the appliance casing, the surface on which it is installed and adjacent surfaces and external temperature of the ducts 64
6.6.1 Requirements 64
6.6.2 Tests 65
6.7 Ignition - Cross-lighting - Flame stability 66
6.7.1 Operation in still air for all appliances 66
6.7.2 Supplementary tests for appliances of types AAS and B1 except for B14 67
6.7.3 Supplementary tests for type C11 appliances and outdoors and/or partially protected appliances 68
6.7.4 Supplementary tests for type C2 appliances 70
6.7.5 Supplementary tests for appliances of types C12, C13, C32, C33, B4 and B5 70
6.7.6 Supplementary tests for type C42 and type C43 appliances 71
6.7.7 Supplementary tests for type C52 and type C53 appliances 71
6.7.8 Supplementary tests for type C6 appliances 71
6.7.9 Supplementary tests for type C72 and type C73 appliances 71
6.7.10 Supplementary tests for type C82 and type C83 appliances 71
6.7.11 Functioning of a permanent ignition burner when the fan stops during the standby time . 72
6.7.12 Air proving device for fan assisted water heaters 72
6.7.13 Functioning of the fan of types C42 and C43 water heaters 75
6.7.14 Protection against the accumulation of gas in the combustion circuit for water heaters equipped with a fan 75
6.7.15 Leakage of combustion products from type C7 water heaters 76
6.7.16 Supplementary tests for type B14, B2 and B3 water heaters 76
6.8 Adjusting, control and safety devices 77
6.8.1 General 77
6.8.2 Control devices 77
6.8.3 Closing mechanisms 77
6.8.4 Ignition devices 79
6.8.5 Safety times 80
6.8.6 Gas pressure regulator 82
6.8.7 Adjustment of the water rate - Maximum water temperature (all appliances) 83
6.8.8 Overheating of the water 83
6.8.9 Effectiveness of the protection against accidental overheating of thermostatic appliances 84
6.8.10 Atmosphere sensing device for type AAS appliances 84

6.8.11 Combustion products discharge safety device of type B11BS appliances 86

Table 3 -- Shutdown times in relation to blockage 87
6.9 Combustion 88
6.9.1 Requirements 88
6.9.2 Test 89

Table 4 -- Percentage of CO2 89
6.9.3 Nitrogen oxides emissions 93

Table 5 -- Weighting factors 94
6.10 Soot deposition 95
6.10.1 Requirement 95
6.10.2 Test 95
6.11 Frost protection system for appliances intended to be installed in a partially protected place 96
6.12 Protection against ingress of rain for appliances intended to be installed in a partially protected place 96
6.13 Condensing water heaters 96
6.13.1 Formation of condensate 96
6.13.2 Temperature of combustion products 97
6.14 Electrical power measurements 97
6.14.1 General 97
6.14.2 Nominal and minimal conditions 97
6.14.3 Standby 98
6.15 Measurement of standby heat losses 98

7 Rational use of energy 98
7.1 General 98
7.2 Heat input of ignition burners 98
7.2.1 Requirement 98
7.2.2 Test 98
7.3 Efficiency 98
7.3.1 Requirement 98
7.3.2 Test 98

8 Fitness for purpose 100
8.1 General 100
8.2 Constructional characteristics 100
8.2.1 Preset water rate adjuster 100
8.2.2 Temperature selector and summer-winter switch 100
8.2.3 Designation and measurement of reference temperatures of flue systems 100
8.2.4 Mechanical resistance and stability of ducts, terminal and fitting pieces 101
8.3 Requirements for plastic in the combustion product evacuation ducts, terminals and fitting pieces for appliances 102
8.3.1 Thermal resistance 102
8.3.2 Materials 103

Table 6 -- Criteria for testing long-term resistance to thermal load 104

Table 7 -- Exposure time in weeks at raised temperatures 104

Table 8 --Criteria for testing long-term resistance to condensate exposure 105

Table 9 -- Composition of test condensate for corrosion 106

Table 10 -- Criteria for testing resistance to condensing/ non- condensing cycling 106
8.4 Requirements for elastomeric seals and elastomeric sealants in the combustion product evacuation ducts, terminals and fitting pieces 108
8.4.1 Characterization 108
8.4.2 Long-term resistance to thermal load 109

Table 11 -- Criteria for testing long-term resistance to thermal load 109
8.4.3 Long-term resistance to condensate exposure 109

Table 12 -- Criteria for testing-long term resistance to condensate exposure 110

Table 13 -- Condensate composition, related to construction classes 110
8.4.4 Cyclic condensate resistance test 110
8.4.5 Relaxation behaviour 111
8.4.6 Compression set 111
8.4.7 Low temperature resistance 111
8.4.8 Joints in elastomeric seals 112
8.5 Operational characteristics 112
8.5.1 Minimum heat input 112
8.5.2 Nominal and minimum useful outputs 112
8.5.3 Ignition of permanent ignition burners by a spark generator 112
8.5.4 Ignition opening time (TIA) 113
8.5.5 Automatic water-operated gas valve 113
8.5.6 Adjustment of the water rate - Water temperature 114

Table 14 -- Maximum permitted deviation for the water rate in relation to the mean rate 115
8.5.7 Heating-up time 118

Table 15 -- Water temperature conditions depending on the control mode of the appliance 119
8.5.8 Specific rate 119

9 Marking and instructions 120
9.1 Water heater marking 120
9.1.1 Data plate 120
9.1.2 Markings related to the state of adjustment 121
9.1.3 Packaging 121
9.1.4 Warnings notices on the water heater and the packaging 122
9.1.5 Other information 123
9.2 Instructions 123
9.2.1 Instructions for installation 123
9.2.2 Instructions for use and servicing 129
9.2.3 Conversion instructions 131
9.3 Presentation 131

10 Nitrogen oxides emissions 132

11 Sound power level (LWA) 132

12 Figures referenced in this standard 133

Figure 1 -- Apparatus for verifying soundness of the gas circuit (see 6.1.6.5, 6.2.1.3 and Annex E) 133

Figure 2 -- Test of an appliance of types B11 and B11BS under abnormal draught conditions (see 6.7.2.2, test n° 1) 134

Figure 3 -- Probe for sampling the combustion products of appliances of types B11 and B11BS (see 6.9.2.1) 135

Figure 4 -- Test of a type C2 appliance mounted on the common duct (see 6.7.4.2) 136

Figure 5 -- Position of the sampling points in the horizontal plane of the sealed room (see 6.8.10.1.2.1 and Annex D) 137

Figure 6 -- Device for sampling the combustion products above the deflector for type AAS appliances (see 6.8.10.2.1.2 and 6.9.2.1) 138

Figure 7 -- Sampling probe for test flues of diameter equal to or greater than DN 100 (see 6.9.2.1) . 139

Figure 8 -- Sampling probe for test flues of diameter less than DN 100 (see 6.9.2.1) 140

Figure 9 -- Probe for sampling and measuring the temperature of the combustion products (see 6.9.2.1) 141

Figure 10 -- Location of the probe for type C appliances (see 6.9.2.1) 142

Figure 11 -- Combustion products discharge safety device for type B11BS appliances (see 6.8.11.4.2.1 and 6.8.11.4.2.2) 143

Figure 12 -- Down-draught test for the type C7 water heaters (see 6.7.9.2 and 6.9.2.4.10) 144

Annex A (informative) National situations 145

A.1 General 145
A.2 Gas connections in common use in the various countries 145

Table A.1 -- Gas connections in common use 146
A.3 Flue pipe diameters in force in the various countries 148

Table A.2 -- Flue pipe diameters marketed 148

Annex B (normative) Test apparatus for type C1, C3, B4 and B5 water heaters (see 6.7.3.2) 149

Figure B.1 -- Test apparatus for type C1, B4 and B5 water heaters fitted with a horizontal terminal installed on a vertical wall 149

Figure B.2 --Test apparatus for type C1, B4 and B5 water heaters fitted with a horizontal terminal installed on an inclined wall 150

Figure B.3 --Test apparatus for type C3, B4 and B5 water heaters fitted with a vertical terminal installed on a horizontal wall 151

Figure B.4 -- Test apparatus for type C3, B4 and B5 water heaters fitted with a vertical terminal installed on an inclined wall 152

Annex C (normative) Test apparatus for type C21 appliances (see 6.7.4.2) 153

Annex D (normative) Description of the sealed room for the tests of type AAS appliances (see 6.8.10.1.2.1) 154

D.1 Configuration of the sealed room 154
D.2 Soundness of the room 154
D.3 Effectiveness of mixing 154
D.4 Equipment of the room 154

Annex E (informative) Soundness of the gas circuit test - Volumetric method (6.2.1) 155

E.1 Equipment 155
E.2 Test method 155

Annex F (informative) Principal symbols and abbreviations used 156

Annex G (informative) Guidelines for extension to other appliances categories 158

Annex H (normative) Lists of materials currently used for the construction of the gas water heaters 159

H.1 General 159
H.2 Special types of steel 159

Table H.1 -- Special types of steel 159

H.3 Copper and copper alloys 159

Table H.2 -- Copper and copper alloys 159
H.4 Plastic materials 160

Table H.3 -- Examples of plastic materials 160

Annex I (normative) Test methods to determine the effects of to long-term thermal load, long-term condensate exposure, condensing/ non-condensing cycling and resistance to UV radiation 161

Annex J (informative) NOx conversion calculation 162

Table J.1 -- Conversion of the emission value of NOx for first family gases 162

Table J.2 -- Conversion of the NOx emission value for second family gases 162

Table J.3 -- Conversion of the NOx emission value for third family gases 162

Table J.4 -- Table of Ratio Gross/Net and Net/Gross for Gas Families 1, 2 and 3 163

Annex K (normative) Parts in copper or copper alloys 164

Table K.1 - Properties of parts in copper or copper alloys 164

Annex L (informative) Compilation of the test conditions for the various gas families 165

Table L.1 - First family 165

Table L.2 - Second family 165

Table L.3 - Third family 166

Annex M (informative) Alternative Method for the determination of the nominal heat input or the maximum and minimum heat input (according to 6.3.1) for appliances using a pneumatic gas/air ratio control system 167

Bibliography 168