

ISO 19882:2025-02 (E)

Gaseous hydrogen - Thermally activated pressure relief devices for compressed hydrogen vehicle fuel containers

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | vi |
| Introduction | | vii |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Service conditions | 3 |
| 4.1 | General | 3 |
| 4.2 | Design service life | 3 |
| 4.3 | Nominal working pressure | 4 |
| 4.4 | Durability test cycles | 4 |
| 4.5 | Temperature range | 4 |
| 5 | Quality assurance | 4 |
| 6 | General requirements | 4 |
| 6.1 | Material requirements | 4 |
| 6.1.1 | General | 4 |
| 6.1.2 | Metallic materials | 4 |
| 6.1.3 | Non-metallic materials | 5 |
| 6.2 | Design requirements | 5 |
| 6.3 | Flow capacity | 5 |
| 6.4 | Failure modes and effects analysis (FMEA) | 6 |
| 7 | Design qualification testing | 6 |
| 7.1 | Test requirements | 6 |
| 7.1.1 | General | 6 |
| 7.1.2 | Test gases | 8 |
| 7.2 | Pressure cycling | 8 |
| 7.2.1 | Sampling | 8 |
| 7.2.2 | Procedure | 8 |
| 7.2.3 | Acceptable results | 9 |
| 7.3 | Accelerated life | 9 |
| 7.3.1 | Sampling | 9 |
| 7.3.2 | Procedure | 9 |
| 7.3.3 | Acceptable results | 9 |
| 7.4 | Thermal cycling | 10 |
| 7.4.1 | Sampling | 10 |
| 7.4.2 | Procedure | 10 |
| 7.4.3 | Acceptable results | 10 |
| 7.5 | Accelerated cyclic corrosion | 10 |
| 7.5.1 | Sampling | 10 |
| 7.5.2 | Procedure | 10 |
| 7.5.3 | Acceptable results | 12 |
| 7.6 | Automotive fluids exposure | 12 |
| 7.6.1 | Sampling | 12 |
| 7.6.2 | Procedure | 12 |

| | | |
|--------|--|----|
| 7.6.3 | Acceptable results | 12 |
| 7.7 | Atmospheric exposure | 13 |
| 7.7.1 | General | 13 |
| 7.7.2 | Oxygen aging | 13 |
| 7.7.3 | Ozone | 13 |
| 7.8 | Stress corrosion cracking resistance | 13 |
| 7.8.1 | Sampling | 13 |
| 7.8.2 | Procedure | 13 |
| 7.8.3 | Acceptable results | 14 |
| 7.9 | Impact due to drop and vibration | 14 |
| 7.9.1 | Impact due to drop | 14 |
| 7.9.2 | Vibration | 14 |
| 7.10 | Leakage | 15 |
| 7.10.1 | Sampling | 15 |
| 7.10.2 | Procedure | 15 |
| 7.10.3 | Acceptable results | 15 |
| 7.11 | Bench top activation | 15 |
| 7.11.1 | Direct-acting TPRD | 15 |
| 7.11.2 | Pilot-activated PRDs | 16 |
| 7.12 | Flow capacity | 17 |
| 7.12.1 | Sampling | 17 |
| 7.12.2 | Procedure | 17 |
| 7.12.3 | Acceptable results | 17 |
| 7.13 | High pressure activation and flow | 18 |
| 7.13.1 | Sampling | 18 |
| 7.13.2 | Procedure | 18 |
| 7.13.3 | Acceptable results | 18 |
| 7.14 | Excess torque resistance | 18 |
| 7.14.1 | Sampling | 18 |
| 7.14.2 | Procedure | 18 |
| 7.14.3 | Acceptable results | 18 |
| 7.15 | Hydrostatic strength | 19 |
| 7.15.1 | Sampling | 19 |
| 7.15.2 | Procedure | 19 |
| 7.15.3 | Acceptable results | 19 |
| 7.16 | Water jet protection | 19 |
| 7.16.1 | Sampling | 19 |
| 7.16.2 | Procedure | 19 |
| 7.16.3 | Acceptable results | 20 |
| 8 | Inspection and acceptance testing | 20 |
| 8.1 | Inspection and acceptance testing plan | 20 |
| 8.2 | Inspector's responsibilities | 20 |
| 8.3 | Inspection of system critical components | 20 |
| 8.4 | Leak testing | 20 |
| 9 | Production batch testing | 20 |
| 9.1 | General | 20 |
| 9.2 | Production batch sizes | 21 |
| 9.2.1 | General | 21 |
| 9.2.2 | Fusible materials | 21 |
| 9.2.3 | Pressure relief devices | 21 |
| 9.3 | Pressure relief device components | 21 |
| 9.4 | Pressure cycle verification | 21 |
| 9.4.1 | General | 21 |
| 9.4.2 | Procedure | 21 |
| 9.4.3 | Acceptable results | 21 |
| 9.5 | Bench top activation | 21 |
| 9.5.1 | General | 21 |
| 9.5.2 | Procedure | 21 |
| 9.5.3 | Acceptable results | 22 |

| | | |
|---|--|-----------|
| 10 | Marking | 22 |
| 10.1 | Required information | 22 |
| 10.2 | Marking methods | 22 |
| 11 | Component literature | 22 |
| 11.1 | General | 22 |
| 11.2 | Component literature recommendations for pilot-activated PRD valves | 23 |
| Annex A (informative) Subsystem and vehicle level considerations | | 24 |
| Annex B (informative) Design qualification test rationale | | 28 |
| Bibliography | | 31 |