

# DIN EN 12864:2006-03 (E)

Low-pressure, non adjustable regulators having a maximum outlet pressure of less than or equal to 200 mbar, with a capacity of less than or equal to 4 kg/h, and their associated safety devices for butane, propane or their mixtures

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>7</b>
<b>3.1</b>	<b>General definitions .....</b>	<b>7</b>
<b>3.2</b>	<b>Definitions concerning gas .....</b>	<b>8</b>
<b>3.3</b>	<b>Definitions concerning pressures .....</b>	<b>8</b>
<b>3.4</b>	<b>Definitions concerning rates .....</b>	<b>9</b>
<b>4</b>	<b>Terminology .....</b>	<b>9</b>
<b>5</b>	<b>Structural characteristics .....</b>	<b>10</b>
<b>5.1</b>	<b>General .....</b>	<b>10</b>
<b>5.2</b>	<b>Materials .....</b>	<b>11</b>
<b>5.3</b>	<b>Special requirements .....</b>	<b>12</b>
<b>5.4</b>	<b>Mechanical strength .....</b>	<b>14</b>
<b>5.5</b>	<b>Soundness .....</b>	<b>15</b>
<b>5.6</b>	<b>Mechanical endurance .....</b>	<b>16</b>
<b>5.7</b>	<b>Resistance to humidity changes .....</b>	<b>16</b>
<b>5.8</b>	<b>Resistance to corrosion .....</b>	<b>16</b>
<b>6</b>	<b>Performance characteristics .....</b>	<b>17</b>
<b>7</b>	<b>Test methods .....</b>	<b>19</b>
<b>7.1</b>	<b>General conditions .....</b>	<b>19</b>
<b>7.2</b>	<b>Verification of structural characteristics .....</b>	<b>20</b>
<b>7.3</b>	<b>Verification of performance characteristics .....</b>	<b>28</b>
<b>8</b>	<b>Marking - Packaging - Instructions .....</b>	<b>32</b>
<b>8.1</b>	<b>General .....</b>	<b>32</b>
<b>8.2</b>	<b>Marking of the regulator .....</b>	<b>32</b>
<b>8.3</b>	<b>Packaging .....</b>	<b>33</b>
<b>8.4</b>	<b>Instructions for use and maintenance .....</b>	<b>33</b>
<b>Annex A (normative) Special requirements for regulators fitted with pressure or rate operated safety devices .....</b>		<b>34</b>
<b>A.1</b>	<b>Regulators fitted with an overpressure relief valve of a limited flow rate .....</b>	<b>34</b>
<b>A.2</b>	<b>Regulators fitted with an overpressure shut off device .....</b>	<b>35</b>
<b>A.3</b>	<b>Regulators fitted with an underpressure shut off safety device .....</b>	<b>37</b>
<b>A.4</b>	<b>Regulators fitted with an excess flow valve .....</b>	<b>38</b>
<b>Annex B (normative) Special requirements for regulators fitted with a temperature operated safety device .....</b>		<b>41</b>
<b>B.1</b>	<b>Definition .....</b>	<b>41</b>
<b>B.2</b>	<b>Structural characteristics .....</b>	<b>41</b>
<b>B.3</b>	<b>Performance characteristics .....</b>	<b>41</b>

<b>B.4</b>	<b>Test methods</b>	<b>41</b>
<b>Annex C (normative)</b>	<b>Special requirements for low pressure regulators under extreme temperature conditions</b>	<b>43</b>
<b>Annex D (normative)</b>	<b>Multimode connection regulator for LPG cylinders to supply appliances installed in caravans and motor caravans or freshwater boats</b>	<b>44</b>
<b>D.1</b>	<b>Scope</b>	<b>44</b>
<b>D.2</b>	<b>Design characteristics</b>	<b>44</b>
<b>D.3</b>	<b>Structural characteristics</b>	<b>45</b>
<b>D.4</b>	<b>Operating characteristics</b>	<b>47</b>
<b>D.5</b>	<b>Marking - Packaging - Instructions</b>	<b>48</b>
<b>Annex E (normative)</b>	<b>Complementary test requirements for non metallic thermoplastic or thermosetting materials used in the construction of regulators</b>	<b>52</b>
<b>E.1</b>	<b>Scope</b>	<b>52</b>
<b>E.2</b>	<b>Materials</b>	<b>52</b>
<b>E.3</b>	<b>Special conditions for carrying out the tests mentioned in the body of the standard</b>	<b>52</b>
<b>E.4</b>	<b>Special requirements</b>	<b>53</b>
<b>E.5</b>	<b>Sampling and order of tests</b>	<b>54</b>
<b>Annex F (normative)</b>	<b>Supplementary requirements for reinforced diaphragms and elastomeric seals used in LPG appliances and their associated equipment</b>	<b>55</b>
<b>Annex G (normative)</b>	<b>Inlet connections</b>	<b>56</b>
<b>Annex H (normative)</b>	<b>Outlet connections</b>	<b>89</b>
<b>Annex I (normative)</b>	<b>Special requirements for low pressure non adjustable regulators fitted with two or three outlets for outdoor use</b>	<b>104</b>
<b>I.1</b>	<b>Structural characteristics</b>	<b>104</b>
<b>I.2</b>	<b>Performance characteristics</b>	<b>104</b>
<b>I.3</b>	<b>Test methods</b>	<b>104</b>
<b>I.4</b>	<b>Marking</b>	<b>106</b>
<b>Annex J (normative)</b>	<b>Method for measuring leaks at test pressures less than or equal to 20 bar</b>	<b>107</b>
<b>J.1</b>	<b>Scope</b>	<b>107</b>
<b>J.2</b>	<b>Diagram of the test bench</b>	<b>107</b>
<b>J.3</b>	<b>Determination of coefficient K</b>	<b>108</b>
<b>J.4</b>	<b>Measurement of the leak</b>	<b>108</b>
<b>J.5</b>	<b>Checks</b>	<b>109</b>
<b>Annex K (normative)</b>	<b>Special requirements for regulators fitted with an inlet valve</b>	<b>110</b>
<b>K.1</b>	<b>Definition</b>	<b>110</b>
<b>K.2</b>	<b>Structural characteristics</b>	<b>110</b>
<b>K.3</b>	<b>Performance characteristics : mechanical strength</b>	<b>110</b>
<b>K.4</b>	<b>Test method</b>	<b>110</b>
<b>Annex L (informative)</b>	<b>Alternative test method for resistance to corrosion</b>	<b>111</b>
<b>L.1</b>	<b>Principle</b>	<b>111</b>
<b>L.2</b>	<b>Reagents</b>	<b>111</b>
<b>L.3</b>	<b>Apparatus</b>	<b>112</b>
<b>L.4</b>	<b>Test method</b>	<b>114</b>
<b>L.5</b>	<b>Results</b>	<b>114</b>
<b>Annex M (normative)</b>	<b>Regulator for LPG cylinders to supply appliances installed in seawater boats</b>	<b>117</b>

<b>M.1</b>	<b>Scope .....</b>	<b>117</b>
<b>M.2</b>	<b>General .....</b>	<b>117</b>
<b>M.3</b>	<b>Maximum guaranteed rate .....</b>	<b>117</b>
<b>M.4</b>	<b>Regulators fitted with a pressure relief valve .....</b>	<b>117</b>
<b>M.5</b>	<b>Vent .....</b>	<b>117</b>
<b>M.6</b>	<b>Connections .....</b>	<b>117</b>
<b>M.7</b>	<b>Material .....</b>	<b>117</b>
<b>M.8</b>	<b>Corrosion .....</b>	<b>118</b>
<b>M.9</b>	<b>Marking .....</b>	<b>118</b>
<b>M.10</b>	<b>Instructions for use and maintenance .....</b>	<b>118</b>
<b>Annex ZA (informative) Clauses of this European Standard addressing essential requirements or other provisions of EU directives .....</b>		<b>119</b>