

ISO 7176-5:2008-06 (E)

Wheelchairs - Part 5: Determination of dimensions, mass and manoeuvring space

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Wheelchair classes and occupant mass groups	22
4.1	General	22
4.2	Classes of electrically powered wheelchairs	22
4.3	Occupant mass groups	22
5	Test apparatus	22
6	Selection of the test wheelchair	26
7	Preparation of the test wheelchair	27
7.1	General	27
7.2	Wheelchair equipment	27
7.3	Wheelchair adjustment	27
7.4	Final check	32
7.5	Positioning	32
7.6	Loading of the wheelchair	32
7.7	Records	34
7.8	Use of hand space gauge and foot space gauges	34
7.9	Wheel rotation	34
7.10	Asymmetrical design of test wheelchair	35
8	Required measurements	35
8.1	General	35
8.2	Full overall length	36
8.3	Overall width	36
8.4	Handgrip height	36
8.5	Stowage length	36
8.6	Stowage width	37
8.7	Stowage height	37
8.8	Rising	37
8.9	Total mass	37
8.10	Mass of heaviest part	37
8.11	Pivot width	38
8.12	Reversing width	38
8.13	Turning diameter	38
8.14	Ground clearance	39
8.15	Required width of angled corridor	39
8.16	Required doorway entry depth	39
8.17	Required corridor width for side opening	39
9	Disclosure of information	41
9.1	General	41

9.2	Wheelchairs with handrims	41
9.3	Wheelchairs without handrims	41
10	Test report	42
10.1	Requirements	42
10.2	Recommendations	43
	Annex A (informative) Technical dimensions	45
	Annex B (informative) Pivot width and reversing width	59
	Annex C (informative) Turning diameter	69
	Annex D (informative) Wheelchair longitudinal axis and wheelchair centre-point	74
	Annex E (informative) Guidelines and recommendations for wheelchair design and performance ...	75
	Bibliography	79