

ISO 7176-19:2008-07 (E)

Wheelchairs - Part 19: Wheeled mobility devices for use as seats in motor vehicles

Contents		Page
Foreword		iv
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Design requirements	6
4.1	Wheelchair securement	6
4.2	Occupant restraints	6
4.2.1	Wheelchair-anchored pelvic-belt restraint	6
4.2.2	Wheelchair-anchored shoulder-belt restraint	8
4.2.3	Accommodation of vehicle-anchored occupant belt restraints	9
5	Performance requirements	10
5.1	Wheelchair-anchored belt restraints	10
5.2	Frontal impact	11
5.2.1	During the test	11
5.2.2	After the test	12
5.3	Accessibility of securement points intended for use with four-point strap-type tiedowns with hook-type end-fittings	13
5.4	Accommodation of vehicle-anchored belt restraints	13
6	Identification, labelling, user instructions, warning, and disclosure requirements	13
6.1	Identification and labelling	13
6.2	Presale literature	14
6.3	User and maintenance instructions	14
7	Documentation of compliance	17
7.1	General	17
7.2	Frontal impact test	17
7.3	Design, labelling, and literature requirements	18
Annex A (normative)	Method for frontal impact test	19
Annex B (normative)	Geometric specifications for securement points on wheelchairs intended for attachment of four-point strap-type tiedowns	27
Annex C (normative)	Method for testing accessibility of wheelchair securement points intended for attachment of four-point strap-type tiedowns	29
Annex D (normative)	Methods for rating wheelchair accommodation of vehicle-anchored belt restraints	32
Annex E (informative)	Guidelines for surrogate tiedown devices	37
Annex F (normative)	Specifications for wheelchair universal docking interface geometry (UDIG)	38
Bibliography		43