ISO/IEEE 11073-10406:2012-12 (E)

Health informatics - Personal health device communication - Part 10406: Device specialization - Basic electrocardiograph (ECG) (1- to 3-lead ECG)

Contents

Page

1. Overview 1
1.1 Scope 1
1.2 Purpose 1
1.3 Context 2

2. Normative references 2

3. Definitions, acronyms, and abbreviations 3
3.1 Definitions 3
3.2 Acronyms and abbreviations 3

4.1 General 4
4.3 Compliance with other standards 5

5. Basic ECG (1- to 3-lead ECG) device concepts and modalities 6
5.1 General 6
5.2 ECG waveform 6
5.3 R-R interval 6
5.4 Heart rate 7

6. Basic ECG (1- to 3-lead ECG) domain information model 7
6.1 Overview 7
6.2 Class extensions 7
6.3 Object instance diagram 7
6.4 Types of configuration 8
6.5 Profiles 9
6.6 Medical device system object 11
6.7 Numeric objects 15
6.8 Real-time sample array objects 18
6.9 Enumeration objects 19
6.10 PM-store objects 22
6.11 Scanner objects 29
6.12 Class extension objects 32
6.13 Basic ECG (1- to 3-lead ECG) information model extensibility rules 32

7. Basic ECG (1- to 3-lead ECG) service model 32
7.1 General 32
7.2 Object access services 32
7.3 Object access event report services 35

8. Basic ECG (1- to 3-lead ECG) communication model 35
8.1 Overview 35
8.2 Communications characteristics 36
8.3 Association procedure 36
8.4 Configuring procedure 38
8.5 Operating procedure 39
8.6 Time synchronization 40

9. Test associations 40
9.1 Behavior with standard configuration 40
9.2 Behavior with extended configurations 41

10. Conformance 41
10.1 Applicability 41
10.2 Conformance specification 41
10.3 Levels of conformance 42
10.4 Implementation conformance statements 42

Annex A (informative) Bibliography 47

Annex B (normative) Any additional ASN.1 definitions 48

Annex C (normative) Allocation of identifiers 49

Annex D (informative) Message sequence examples 50

Annex E (informative) Protocol data unit examples 52