ISO 10555-6:2015-04 (E)

Intravascular catheters - Sterile and single-use catheters - Part 6: Subcutaneous implanted ports

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Requirements of the implantable subcutaneous implanted port and catheter 3
4.1 General 3
4.2 Biocompatibility 4
4.3 Distance markings 4
4.4 Nominal dimensions of the subcutaneous implanted port 4
4.5 Physical requirements 4
4.5.1 Radio-detectability 4
4.5.2 Surface finish 4
4.5.3 Freedom from leakage 4
4.5.4 Flushing volume 4
4.5.5 Characteristics of the septum 5
4.5.6 Characteristics of the connection or the catheter 5
4.6 Flow rate 5
4.6.1 Subcutaneous implanted ports not indicated for power injection 5
4.6.2 Subcutaneous implanted ports indicated for power injection 5
4.7 Burst pressure of the subcutaneous implanted port and catheter 6
4.7.1 Subcutaneous implanted ports not indicated for power injection 6
4.7.2 Subcutaneous implanted ports indicated for power injection 6

5 Magnetic Resonance Imaging (MRI) compatibility 6

6 Information to be supplied by the manufacturer 6
6.1 Marking on the device 6
6.2 Primary packaging 6
6.3 Labels for traceability 7
6.4 Instruction for use 7

Annex A (normative) Test method for freedom from air leakage 8

Annex B (informative)Determinationofflushingvolume 10

Annex C (informative) Guidance on further characterization testing: Needle penetration and withdrawal 12

Annex D (normative) Test method for freedom from leakage after multiple punctures 14

Annex E (normative) Peak tensile force 15

Bibliography 16